



UTS6FC14E5S Information

Part Number UTS6FC14E5S

Manufacturer Souriau

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 5POS CABLE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UTS6FC14E5S Specifications

Manufacturer Part NumberUTS6FC14E5SManufacturerSouriauCategoryConnectors, InterconnectsPackage-SeriesTrim Trio? UTS Hi SealConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating12A		
Category Circular Connectors Package - Series Trim Trio? UTS Hi Seal Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated Circular Connectors Trim Trio? UTS Hi Seal - Connectors Trim Trio? UTS Hi Seal Free Haseal Sockets Number Solder Sol	Manufacturer Part Number	UTS6FC14E5S
Package-SeriesTrim Trio? UTS Hi SealConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating12A	Manufacturer	Souriau
Package-SeriesTrim Trio? UTS Hi SealConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating12A	Category	Connectors, Interconnects
SeriesTrim Trio? UTS Hi SealConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating12A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating12A	Package	-
Number of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating12A	Series	Trim Trio? UTS Hi Seal
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 12A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 12A	Number of Positions	5
Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 12A	Shell Size - Insert	14-5
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 12A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 12A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 12A	Termination	Solder Cup
Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Contact Finish Gold Features Backshell Voltage - Rated Current Rating 12A	Fastening Type	Bayonet Lock
Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 12A	Orientation	N (Normal)
Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 12A	Ingress Protection	IP68/69K - Dust Tight, Water Resistant, Waterproof
Features Backshell Voltage - Rated 650V Current Rating 12A	Shell Material, Finish	Polyamide (PA), Nylon
Voltage - Rated 650V Current Rating 12A	Contact Finish	Gold
Current Rating 12A	Features	Backshell
•	Voltage - Rated	650V
Report errors?	Current Rating	12A
		Report errors?

UTS6FC14E5S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UTS6FC14E5S Payment Methods



















UTS6FC14E5S Shipping Methods













If you have any question about UTS6FC14E5S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com