



UTS7124SSCR Information



For Reference Only

Part Number UTS7124SSCR

Manufacturer Souriau

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT JAM NUT 4POS F SCREW

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UTS7124SSCR Specifications

Manufacturer Part Number UTS7124SSCR Manufacturer Souriau Category Connectors, Interconnects Circular Connectors Package - Series Trim Trio? UTS Connector Type Receptacle, Female Sockets Number of Positions 4 (3 + PE) Shell Size - Insert 12-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Screw Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 500V Current Rating 10A			
CategoryConnectors, InterconnectsPackage-SeriesTrim Trio? UTSConnector TypeReceptacle, Female SocketsNumber of Positions4 (3 + PE)Shell Size - Insert12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationScrewFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A	Manufacturer Part Number	UTS7124SSCR	
Package-SeriesTrim Trio? UTSConnector TypeReceptacle, Female SocketsNumber of Positions4 (3 + PE)Shell Size - Insert12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationScrewFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A	Manufacturer	Souriau	
Package-SeriesTrim Trio? UTSConnector TypeReceptacle, Female SocketsNumber of Positions4 (3 + PE)Shell Size - Insert12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationScrewFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A	Category	Connectors, Interconnects	
SeriesTrim Trio? UTSConnector TypeReceptacle, Female SocketsNumber of Positions4 (3 + PE)Shell Size - Insert12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationScrewFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A		Circular Connectors	
Connector Type Receptacle, Female Sockets Number of Positions 4 (3 + PE) Shell Size - Insert 12-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Screw Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Gold Features - Voltage - Rated 500V Current Rating 10A	Package	-	
Number of Positions4 (3 + PE)Shell Size - Insert12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationScrewFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A	Series	Trim Trio? UTS	
Shell Size - Insert12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationScrewFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A	Connector Type	Receptacle, Female Sockets	
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Screw Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 500V Current Rating 10A	Number of Positions	4 (3 + PE)	
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationScrewFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A	Shell Size - Insert	12-4	
Termination Screw Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 500V Current Rating 10A	Shell Size, MIL	-	
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 500V Current Rating 10A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut	
Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 500V Current Rating 10A	Termination	Screw	
Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Thermoplastic Contact Finish Gold Features - Voltage - Rated Current Rating IP68/69K - Dust Tight, Water Resistant, Waterproof Thermoplastic 500V 10A	Fastening Type	Bayonet Lock	
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 10A	Orientation	N (Normal)	
Contact Finish Gold Features - Voltage - Rated 500V Current Rating 10A	Ingress Protection	IP68/69K - Dust Tight, Water Resistant, Waterproof	
Features - Voltage - Rated 500V Current Rating 10A	Shell Material, Finish	Thermoplastic	
Voltage - Rated 500V Current Rating 10A	Contact Finish	Gold	
Current Rating 10A	Features	-	
	Voltage - Rated	500V	
	Current Rating	10A	
Report errors?		Report erro	rs?

UTS7124SSCR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UTS7124SSCR Payment Methods



















UTS7124SSCR Shipping Methods













If you have any question about UTS7124SSCR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com