



### **UTS712D10P Information**



For Reference Only

Part Number UTS712D10P Manufacturer Souriau

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 10POS PANEL TH PIN

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UTS712D10P Specifications**

Manufacturer Part NumberUTS712D10PManufacturerSouriauCategoryConnectors, InterconnectsPackage-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4.5A	•	
CategoryConnectors, InterconnectsPackage-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4.5A	Manufacturer Part Number	UTS712D10P
Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4.5A	Manufacturer	Souriau
Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4.5A	Category	Connectors, Interconnects
SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4.5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4.5A	Package	-
Number of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4.5A	Series	Trim Trio? UTS Hi Seal
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Bulkhead; Through Hole  Termination  Solder  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP68/69K - Dust Tight, Water Resistant, Waterproof  Shell Material, Finish  Thermoplastic  Contact Finish  Gold  Features  Board Lock  Voltage - Rated  250V  Current Rating  4.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead; Through Hole  Termination Solder  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold  Features Board Lock  Voltage - Rated 250V  Current Rating 4.5A	Number of Positions	10
Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBoard LockVoltage - Rated250VCurrent Rating4.5A	Shell Size - Insert	12-10
Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4.5A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Contact Finish  Gold  Features  Board Lock  Voltage - Rated  Current Rating  Bayonet Lock  N (Normal)  IP68/69K - Dust Tight, Water Resistant, Waterproof  Thermoplastic  Gold  Board Lock  Voltage - Rated  250V  4.5A	Mounting Type	Panel Mount, Bulkhead; Through Hole
Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4.5A	Termination	Solder
Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Board Lock Voltage - Rated Current Rating 4.5A	Orientation	N (Normal)
Contact Finish Gold Features Board Lock Voltage - Rated 250V Current Rating 4.5A	Ingress Protection	IP68/69K - Dust Tight, Water Resistant, Waterproof
Features Board Lock Voltage - Rated 250V Current Rating 4.5A	Shell Material, Finish	Thermoplastic
Voltage - Rated 250V Current Rating 4.5A	Contact Finish	Gold
Current Rating 4.5A	Features	Board Lock
-	Voltage - Rated	250V
Report errors?	Current Rating	4.5A
		Report errors?

#### **UTS712D10P Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UTS712D10P Payment Methods**



















### **UTS712D10P Shipping Methods**













If you have any question about UTS712D10P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com