



UTS714D18S Information

Part Number UTS714D18S

Manufacturer Souriau

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 18POS JAM NUT SKT PCB

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UTS714D18S Specifications

| Manufacturer Part NumberUTS714D18SManufacturerSouriauCategoryConnectors, InterconnectsPackage-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions18Shell Size - Insert14-18Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent RatingPaport arrange | | | |
|--|--------------------------|--|-----|
| CategoryConnectors, InterconnectsPackage-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions18Shell Size - Insert14-18Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating4A | Manufacturer Part Number | UTS714D18S | |
| Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions18Shell Size - Insert14-18Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating4A | Manufacturer | Souriau | |
| Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions18Shell Size - Insert14-18Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating4A | Category | Connectors, Interconnects | |
| SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions18Shell Size - Insert14-18Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating4A | | Circular Connectors | |
| Connector TypeReceptacle, Female SocketsNumber of Positions18Shell Size - Insert14-18Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating4A | Package | - | |
| Number of Positions18Shell Size - Insert14-18Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating4A | Series | Trim Trio? UTS Hi Seal | |
| Shell Size - Insert Shell Size, MIL | Connector Type | Receptacle, Female Sockets | |
| Shell Size, MIL Mounting Type Panel Mount, Bulkhead; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 250V Current Rating 4A | Number of Positions | 18 | |
| Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating4A | Shell Size - Insert | 14-18 | |
| Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 250V Current Rating 4A | Shell Size, MIL | - | |
| Fastening Type Orientation N (Normal) Ingress Protection Shell Material, Finish Contact Finish Gold Features Voltage - Rated Current Rating Bayonet Lock N (Normal) IP68/69K - Dust Tight, Water Resistant, Waterproof Thermoplastic Gold - Voltage - Rated 4A | Mounting Type | Panel Mount, Bulkhead; Through Hole | |
| Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 250V Current Rating 4A | Termination | Solder | |
| Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 250V Current Rating 4A | Fastening Type | Bayonet Lock | |
| Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 4A | Orientation | N (Normal) | |
| Contact Finish Gold Features - Voltage - Rated 250V Current Rating 4A | Ingress Protection | IP68/69K - Dust Tight, Water Resistant, Waterproof | |
| Features - Voltage - Rated 250V Current Rating 4A | Shell Material, Finish | Thermoplastic | |
| Voltage - Rated 250V Current Rating 4A | Contact Finish | Gold | |
| Current Rating 4A | Features | - | |
| | Voltage - Rated | 250V | |
| Danast arrars? | Current Rating | 4A | |
| Report errors? | | Report error | rs? |

UTS714D18S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UTS714D18S Payment Methods



















UTS714D18S Shipping Methods













If you have any question about UTS714D18S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com