



### **UTS714D5P Information**

Part Number UTS714D5P Manufacturer Souriau

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 5POS JAM NUT PIN PCB

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UTS714D5P Specifications**

Manufacturer Part Number     UTS714D5P       Manufacturer     Souriau       Category     Connectors, Interconnects       Package     -       Series     Trim Trio? UTS Hi Seal       Connector Type     Receptacle, Male Pins       Number of Positions     5       Shell Size - Insert     14-5       Shell Size, MIL     -       Mounting Type     Panel Mount, Bulkhead; Through Hole       Termination     Solder       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     IP68/69K - Dust Tight, Water Resistant, Waterproof       Shell Material, Finish     Thermoplastic       Contact Finish     Gold       Features     -       Voltage - Rated     650V       Current Rating     12A		
CategoryConnectors, InterconnectsPackage-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A	Manufacturer Part Number	UTS714D5P
Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A	Manufacturer	Souriau
Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A	Category	Connectors, Interconnects
SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A		Circular Connectors
Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Gold Features - Voltage - Rated 650V Current Rating 12A	Package	-
Number of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A	Series	Trim Trio? UTS Hi Seal
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 650V Current Rating 14-5  Panel Mount, Bulkhead; Through Hole - Rated Golder - Coverable Material, Finish Gold - Current Rating 12A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead; Through Hole  Termination Solder  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 650V Current Rating 12A	Number of Positions	5
Mounting Type Panel Mount, Bulkhead; Through Hole  Termination Solder  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof  Shell Material, Finish Thermoplastic  Contact Finish Gold  Features -  Voltage - Rated 650V  Current Rating 12A	Shell Size - Insert	14-5
Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 650V Current Rating 12A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 650V Current Rating 12A	Mounting Type	Panel Mount, Bulkhead; Through Hole
Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 650V Current Rating 12A	Termination	Solder
Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 650V Current Rating 12A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 12A Thermoplastic  650V  12A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 650V Current Rating 12A	Ingress Protection	IP68/69K - Dust Tight, Water Resistant, Waterproof
Features - Voltage - Rated 650V Current Rating 12A	Shell Material, Finish	Thermoplastic
Voltage - Rated 650V Current Rating 12A	Contact Finish	Gold
Current Rating 12A	Features	-
	Voltage - Rated	650V
Report errors?	Current Rating	12A
· · · · · · · · · · · · · · · · · · ·		Report errors?

#### **UTS714D5P Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UTS714D5P Payment Methods**



















## **UTS714D5P Shipping Methods**













If you have any question about UTS714D5P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com