



## **UTS78E3S Information**

**Part Number** UTS78E3S **Manufacturer** Souriau

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 3POS JAM NUT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **UTS78E3S Specifications**

Manufacturer Part Number     UTS78E3S       Manufacturer     Souriau       Category     Connectors, Interconnects       Package     -       Series     Trim Trio? UTS Hi Seal       Connector Type     Receptacle, Female Sockets       Number of Positions     3       Shell Size - Insert     8-3       Shell Size, MIL     -       Mounting Type     Panel Mount, Bulkhead - Front Side Nut       Termination     Solder Cup       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     IP68/69K - Dust Tight, Water Resistant, Waterproof       Shell Material, Finish     Thermoplastic       Contact Finish     Gold       Features     -       Voltage - Rated     250V       Current Rating     7A			
CategoryConnectors, InterconnectsPackage-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert8-3Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating7A	Manufacturer Part Number	UTS78E3S	
Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert8-3Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating7A	Manufacturer	Souriau	
Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert8-3Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating7A	Category	Connectors, Interconnects	
SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert8-3Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating7A		Circular Connectors	
Connector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert8-3Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating7A	Package	-	
Number of Positions3Shell Size - Insert8-3Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating7A	Series	Trim Trio? UTS Hi Seal	
Shell Size - Insert8-3Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating7A	Connector Type	Receptacle, Female Sockets	
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 250V Current Rating 7A	Number of Positions	3	
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating7A	Shell Size - Insert	8-3	
Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 250V Current Rating 7A	Shell Size, MIL	-	
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  IP68/69K - Dust Tight, Water Resistant, Waterproof  Thermoplastic  Contact Finish  Gold  Features  -  Voltage - Rated  250V  Current Rating  7A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut	
Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 250V Current Rating 7A	Termination	Solder Cup	
Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 7A	Fastening Type	Bayonet Lock	
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 7A	Orientation	N (Normal)	
Contact Finish Gold Features - Voltage - Rated 250V Current Rating 7A	Ingress Protection	IP68/69K - Dust Tight, Water Resistant, Waterproof	
Features - Voltage - Rated 250V Current Rating 7A	Shell Material, Finish	Thermoplastic	
Voltage - Rated 250V Current Rating 7A	Contact Finish	Gold	
Current Rating 7A	Features	-	
-	Voltage - Rated	250V	
Report errors?	Current Rating	7A	
		Report error	s?

### **UTS78E3S Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UTS78E3S Payment Methods**





















## **UTS78E3S Shipping Methods**













If you have any question about UTS78E3S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com