

UUD1H3R3MCR1GS

UUD1H3R3MCR1GS Information



For Reference Only

Part Number UUD1H3R3MCR1GS

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 3.3UF 20% 50V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UUD1H3R3MCR1GS Specifications

Manufacturer Part Number UUD1H3R3MCR1GS Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series UUD Capacitance 3.3µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15mA @ 120Hz Ripple Current - High Frequency 30mA @ 100kHz Impedance 5 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	ı	
Category Capacitors Package Radial, Can - SMD Series UUD Capacitance 3.3µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15mA @ 120Hz Ripple Current - High Frequency 30mA @ 100kHz Impedance 5 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer Part Number	UUD1H3R3MCR1GS
Package Radial, Can - SMD Series UUD Capacitance 3.3μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15mA @ 120Hz Ripple Current - High Frequency 30mA @ 100kHz Impedance 5 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer	Nichicon
Package Radial, Can - SMD Series UUD Capacitance 3.3µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15mA @ 120Hz Ripple Current - High Frequency 30mA @ 100kHz Impedance 5 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Category	Capacitors
Series UUD Capacitance 3.3µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15mA @ 120Hz Ripple Current - High Frequency 30mA @ 100kHz Impedance 5 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD		Aluminum Electrolytic Capacitors
Capacitance3.3μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15mA @ 120HzRipple Current - High Frequency30mA @ 100kHzImpedance5 OhmsLead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.228" (5.80mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Package	Radial, Can - SMD
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15mA @ 120Hz Ripple Current - High Frequency 30mA @ 100kHz Impedance 5 0hms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Series	UUD
Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15mA @ 120Hz Ripple Current - High Frequency 30mA @ 100kHz Impedance 5 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Capacitance	3.3µF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 15mA @ 120Hz Ripple Current - High Frequency 30mA @ 100kHz Impedance 5 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 30mA @ 120Hz Rippedance 5 Ohms Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Voltage - Rated	50V
Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 30mA @ 120Hz 30mA @ 100kHz Impedance 5 Ohms Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Package / Case Radial, Can - SMD	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Soma @ 100kHz Soma @ 100kHz	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 30mA @ 100kHz Impedance 5 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 30mA @ 100kHz Impedance 5 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Polarization	Polar
Ripple Current - High Frequency 30mA @ 100kHz Impedance 5 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Applications	General Purpose
Impedance 5 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - Low Frequency	15mA @ 120Hz
Lead Spacing - O.157" Dia (4.00mm) Height - Seated (Max) O.228" (5.80mm) Surface Mount Land Size O.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - High Frequency	30mA @ 100kHz
Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.228" (5.80mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Impedance	5 Ohms
Height - Seated (Max) Surface Mount Land Size 0.228" (5.80mm) 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Lead Spacing	-
Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Size / Dimension	0.157" Dia (4.00mm)
Mounting Type Surface Mount Package / Case Radial, Can - SMD	Height - Seated (Max)	0.228" (5.80mm)
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.169" L x 0.169" W (4.30mm x 4.30mm)
	Mounting Type	Surface Mount
Report errors?	Package / Case	Radial, Can - SMD
Topot motor.		Report errors?

UUD1H3R3MCR1GS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UUD1H3R3MCR1GS Payment Methods



















UUD1H3R3MCR1GS Shipping Methods













If you have any question about UUD1H3R3MCR1GS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com