

## **UV-405-TO92 Information**

Heisener.com

Part Number UV-405-TO92 Manufacturer Bivar Inc.

**Category** Optoelectronics

LED Indication - Discrete

**Description** LED BLUE CLEAR TO226-2 THRU HOLE

**Package** TO-226-2, TO-92-2 (TO-226AC)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UV-405-TO92 Specifications**

Manufacturer Part Number         UV-405-TO92           Manufacturer         Bivar Inc.           Category         Optoelectronics           LED Indication - Discrete           Package         TO-226-2, TO-92-2 (TO-226AC)           Series         -           Color         Blue           Configuration         -           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         -           Lens Style/Size         Round with Domed Top, 4.80mm           Voltage - Forward (Vf) (Typ)         3.7V           Current - Test         20mA           Viewing Angle         30°           Mounting Type         Through Hole           Wavelength - Dominant         430nm           Wavelength - Peak         405nm           Features         -           Supplier Device Package         TO-92-2 (TO-226AC)           Supplier Device Package         TO-92-2 (TO-226AC)           Size / Dimension         -           Height (Max)         7.00mm	6 v-405-1 672 Specifications	
Category         Optoelectronics           Package         TO-226-2, TO-92-2 (TO-226AC)           Series         -           Color         Blue           Configuration         -           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         -           Lens Style/Size         Round with Domed Top, 4.80mm           Voltage - Forward (Vf) (Typ)         3.7V           Current - Test         20mA           Viewing Angle         30°           Mounting Type         Through Hole           Wavelength - Dominant         430nm           Wavelength - Peak         405nm           Features         -           Package / Case         TO-226-2, TO-92-2 (TO-226AC)           Supplier Device Package         TO-92           Size / Dimension         -           Height (Max)         7.00mm	Manufacturer Part Number	UV-405-TO92
Package         TO-226-2, TO-92-2 (TO-226AC)           Series         -           Color         Blue           Configuration         -           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         -           Lens Style/Size         Round with Domed Top, 4.80mm           Voltage - Forward (Vf) (Typ)         3.7V           Current - Test         20mA           Viewing Angle         30°           Mounting Type         Through Hole           Wavelength - Dominant         430nm           Wavelength - Peak         405nm           Features         -           Package / Case         TO-226-2, TO-92-2 (TO-226AC)           Supplier Device Package         TO-92           Size / Dimension         -           Height (Max)         7.00mm	Manufacturer	Bivar Inc.
Package         TO-226-2, TO-92-2 (TO-226AC)           Series         -           Color         Blue           Configuration         -           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         -           Lens Style/Size         Round with Domed Top, 4.80mm           Voltage - Forward (Vf) (Typ)         3.7V           Current - Test         20mA           Viewing Angle         30°           Mounting Type         Through Hole           Wavelength - Dominant         430nm           Wavelength - Peak         405nm           Features         -           Package / Case         TO-226-2, TO-92-2 (TO-226AC)           Supplier Device Package         TO-92           Size / Dimension         -           Height (Max)         7.00mm	Category	Optoelectronics
Series         -           Color         Blue           Configuration         -           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         -           Lens Style/Size         Round with Domed Top, 4.80mm           Voltage - Forward (Vf) (Typ)         3.7V           Current - Test         20mA           Viewing Angle         30°           Mounting Type         Through Hole           Wavelength - Dominant         430nm           Wavelength - Peak         405nm           Features         -           Package / Case         TO-226-2, TO-92-2 (TO-226AC)           Supplier Device Package         TO-92           Size / Dimension         -           Height (Max)         7.00mm		LED Indication - Discrete
Color         Blue           Configuration         -           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         -           Lens Style/Size         Round with Domed Top, 4.80mm           Voltage - Forward (Vf) (Typ)         3.7V           Current - Test         20mA           Viewing Angle         30°           Mounting Type         Through Hole           Wavelength - Dominant         430nm           Wavelength - Peak         405nm           Features         -           Package / Case         TO-226-2, TO-92-2 (TO-226AC)           Supplier Device Package         TO-92           Size / Dimension         -           Height (Max)         7.00mm	Package	TO-226-2, TO-92-2 (TO-226AC)
Configuration-Lens ColorColorlessLens TransparencyClearMillicandela Rating-Lens Style/SizeRound with Domed Top, 4.80mmVoltage - Forward (Vf) (Typ)3.7VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant430nmWavelength - Peak405nmFeatures-Package / CaseTO-226-2, TO-92-2 (TO-226AC)Supplier Device PackageTO-92Size / Dimension-Height (Max)7.00mm	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating-Lens Style/SizeRound with Domed Top, 4.80mmVoltage - Forward (Vf) (Typ)3.7VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant430nmWavelength - Peak405nmFeatures-Package / CaseTO-226-2, TO-92-2 (TO-226AC)Supplier Device PackageTO-92Size / Dimension-Height (Max)7.00mm	Color	Blue
Lens TransparencyClearMillicandela Rating-Lens Style/SizeRound with Domed Top, 4.80mmVoltage - Forward (Vf) (Typ)3.7VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant430nmWavelength - Peak405nmFeatures-Package / CaseTO-226-2, TO-92-2 (TO-226AC)Supplier Device PackageTO-92Size / Dimension-Height (Max)7.00mm	Configuration	-
Millicandela Rating-Lens Style/SizeRound with Domed Top, 4.80mmVoltage - Forward (Vf) (Typ)3.7VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant430nmWavelength - Peak405nmFeatures-Package / CaseTO-226-2, TO-92-2 (TO-226AC)Supplier Device PackageTO-92Size / Dimension-Height (Max)7.00mm	Lens Color	Colorless
Lens Style/SizeRound with Domed Top, 4.80mmVoltage - Forward (Vf) (Typ)3.7VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant430nmWavelength - Peak405nmFeatures-Package / CaseTO-226-2, TO-92-2 (TO-226AC)Supplier Device PackageTO-92Size / Dimension-Height (Max)7.00mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ)3.7VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant430nmWavelength - Peak405nmFeatures-Package / CaseTO-226-2, TO-92-2 (TO-226AC)Supplier Device PackageTO-92Size / Dimension-Height (Max)7.00mm	Millicandela Rating	-
Current - Test 20mA  Viewing Angle 30°  Mounting Type Through Hole  Wavelength - Dominant 430nm  Wavelength - Peak 405nm  Features - Package / Case TO-226-2, TO-92-2 (TO-226AC)  Supplier Device Package TO-92  Size / Dimension - Height (Max) 7.00mm	Lens Style/Size	Round with Domed Top, 4.80mm
Viewing Angle30°Mounting TypeThrough HoleWavelength - Dominant430nmWavelength - Peak405nmFeatures-Package / CaseTO-226-2, TO-92-2 (TO-226AC)Supplier Device PackageTO-92Size / Dimension-Height (Max)7.00mm	Voltage - Forward (Vf) (Typ)	3.7V
Mounting Type Through Hole  Wavelength - Dominant 430nm  Wavelength - Peak 405nm  Features - Package / Case TO-226-2, TO-92-2 (TO-226AC)  Supplier Device Package TO-92  Size / Dimension - Height (Max) Through Hole 700mm	Current - Test	20mA
Wavelength - Dominant  Wavelength - Peak  405nm  Features  - Package / Case  TO-226-2, TO-92-2 (TO-226AC)  Supplier Device Package  TO-92  Size / Dimension  - Height (Max)  Toomm	Viewing Angle	30°
Wavelength - Peak 405nm  Features - Package / Case TO-226-2, TO-92-2 (TO-226AC)  Supplier Device Package TO-92  Size / Dimension - Height (Max) 7.00mm	Mounting Type	Through Hole
Features - Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package TO-92 Size / Dimension - Height (Max) 7.00mm	Wavelength - Dominant	430nm
Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package TO-92 Size / Dimension - Height (Max) 7.00mm	Wavelength - Peak	405nm
Supplier Device Package TO-92 Size / Dimension - Height (Max) 7.00mm	Features	-
Size / Dimension - Height (Max) 7.00mm	Package / Case	TO-226-2, TO-92-2 (TO-226AC)
Height (Max) 7.00mm	Supplier Device Package	TO-92
	Size / Dimension	-
Report errors?	Height (Max)	7.00mm
		Report errors?

#### **UV-405-TO92 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UV-405-TO92 Payment Methods**



















## **UV-405-TO92 Shipping Methods**













If you have any question about UV-405-TO92, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com