

UVK1A332MHD

UVK1A332MHD Information

wow.hetslener.com	Part Number Manufacturer Category Description Package	Capacitors Aluminum Electrolytic Capacitors CAP ALUM 3300UF 20% 10V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVK1A332MHD Specifications

ManufacturerNichiconCagacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUVKCapacitance3300µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.6675A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUVKCapacitance3300µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.6675A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	UVK1A332MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVKCapacitance330µFTolerance±20%Voltage - RatedIOVESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.6675A @ 10kHzRipple Current - High Frequency0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension0.866" (22.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUVKCapacitance330µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency1.6675A @ 10kHzRiple Current - High Frequency0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension0.866" (22.00mm)Strace Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUVKCapacitance330µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzInpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance3300µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.6675 A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Pokage / CaseRidia, Can	Series	UVK
Voltage - RatedIOVESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency1.6675A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	3300µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Pounting TypeFarough Lande ManagementPackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency1.6675A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	10V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.45A @ 120Hz Ripple Current - High Frequency 1.6675A @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Furough Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency1.6675A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency1.6675A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.45A @ 120HzRipple Current - High Frequency1.6675A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency1.6675A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.45A @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.6675A @ 10kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
*		Report errors?

UVK1A332MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVK1A332MHD Payment Methods



UVK1A332MHD Shipping Methods



If you have any question about UVK1A332MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com