



### **UVK1J222MHD Information**



For Reference Only

Part Number UVK1J222MHD

Manufacturer Nichicon
Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 2200UF 20% 63V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **UVK1J222MHD Specifications**

Manufacturer Part Number         UVK1/222MHD           Manufacturer         Nichicon           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         UVK           Capacitance         2200µF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2,3A @ 120Hz           Ripple Current - High Frequency         2,645A @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.476" (37.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		
Category         Capacitors           Package         Radial, Can           Series         UVK           Capacitance         2200µF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.3A @ 120Hz           Ripple Current - High Frequency         2.645A @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.476" (37.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	UVK1J222MHD
Package         Radial, Can           Series         UVK           Capacitance         2200μF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.3A @ 120Hz           Ripple Current - High Frequency         2.645A @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.476" (37.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	Nichicon
Package         Radial, Can           Series         UVK           Capacitance         2200µF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.3A @ 120Hz           Ripple Current - High Frequency         2.645A @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.476" (37.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         UVK           Capacitance         2200µF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.3A @ 120Hz           Ripple Current - High Frequency         2.645A @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.476" (37.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         2200μF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.3A @ 120Hz           Ripple Current - High Frequency         2.645A @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.476" (37.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 63V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 2.3A @ 120Hz Ripple Current - High Frequency 2.645A @ 10kHz  Impedance - Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.709" Dia (18.00mm)  Height - Seated (Max) 1.476" (37.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	UVK
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  2.3A @ 120Hz  Ripple Current - High Frequency  2.645A @ 10kHz  Impedance  -  Lead Spacing  0.295" (7.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Capacitance	2200μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  2.3A @ 120Hz  Ripple Current - High Frequency  2.645A @ 10kHz  Impedance  -  Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.709" Dia (18.00mm)  Height - Seated (Max)  1.476" (37.50mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  2.3A @ 120Hz  Ripple Current - High Frequency  2.645A @ 10kHz  Impedance  - Lead Spacing  0.295" (7.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  2000 Hrs @ 85°C  -40°C ~ 85°C  Folarization  Oeneral Purpose  2.3A @ 120Hz  2.645A @ 10kHz  -  1.476" (37.50mm)  Through Hole  Radial, Can	Voltage - Rated	63V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.3A @ 120Hz Ripple Current - High Frequency 2.645A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.476" (37.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.3A @ 120Hz  Ripple Current - High Frequency 2.645A @ 10kHz  Impedance -  Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.709" Dia (18.00mm)  Height - Seated (Max) 1.476" (37.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 2.3A @ 120Hz Ripple Current - High Frequency 2.645A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.476" (37.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  2.645A @ 10kHz  Impedance  - Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.709" Dia (18.00mm)  Height - Seated (Max)  1.476" (37.50mm)  Surface Mount Land Size  - Mounting Type  Through Hole  Package / Case  Radial, Can	Polarization	Polar
Ripple Current - High Frequency  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  2.645A @ 10kHz	Applications	General Purpose
Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.476" (37.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	2.3A @ 120Hz
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.476" (37.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	2.645A @ 10kHz
Size / Dimension 0.709" Dia (18.00mm)  Height - Seated (Max) 1.476" (37.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.476" (37.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
1		Report errors?

### **UVK1J222MHD Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UVK1J222MHD Payment Methods**





















### **UVK1J222MHD Shipping Methods**













If you have any question about UVK1J222MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com