

UVK2G221MRD

Request a Quote

UVK2G221MRD Information

	Part Number Manufacturer Category	UVK2G221MRD Nichicon Capacitors	
www.helsener.com	Description Package	Aluminum Electrolytic Capacitors CAP ALUM 220UF 20% 400V RADIAL Radial, Can	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVK2G221MRD Specifications

Manufacturer Part NumberUVK2G221MRDManufacturerNichiconCategoryCapacitorsCategoryCapacitorsPackageRadial, CanPackageRadial, CanSeriesUVKCapacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Operating Temperature9000 Hrs@ 85°CPolarizationSeriesApplicationsGeneral PurposeRipple Current - Low Frequency650mA @ 120HzManufacture.Lad Spacing0.394" (10.00mm)With the function of the Unit of the Construction of the Unit of the Unit of the Construction of the Unit of t	
CategoryCapacitorsCategoryAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUVKCapacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature9000 Hrs @ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency650mA @ 120HzRipple Current - High Frequency1.04A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)	
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesUVKCapacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.04A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)	
PackageRadial, CanSeriesUVKCapacitance220μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency1.04A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)	
SeriesUVKCapacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency650mA @ 120HzImpedance-Lead Spacing0.394" (10.00mm)	
Capacitance220μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency650mA @ 120HzImpedance-Lead Spacing0.394" (10.00mm)	
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency650mA @ 120HzRipple Current - High Frequency1.04A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)	
Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency650mA @ 120HzRipple Current - High Frequency1.04A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)	
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency650mA @ 120HzRipple Current - High Frequency1.04A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)	
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency650mA @ 120HzRipple Current - High Frequency1.04A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)	
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency650mA @ 120HzRipple Current - High Frequency1.04A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)	
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency650mA @ 120HzRipple Current - High Frequency1.04A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)	
ApplicationsGeneral PurposeRipple Current - Low Frequency650mA @ 120HzRipple Current - High Frequency1.04A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)	
Ripple Current - Low Frequency650mA @ 120HzRipple Current - High Frequency1.04A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)	
Ripple Current - High Frequency1.04A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)	
Impedance-Lead Spacing0.394" (10.00mm)	
Lead Spacing 0.394" (10.00mm)	
Size / Dimension 0.866" Dia (22.00mm)	
Height - Seated (Max) 2.047" (52.00mm)	
Surface Mount Land Size -	
Mounting Type Through Hole	
Package / Case Radial, Can	
	Report errors?

UVK2G221MRD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVK2G221MRD Payment Methods



UVK2G221MRD Shipping Methods



If you have any question about UVK2G221MRD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com