



UVP1A472MHD Information



For Reference Only

Part Number UVP1A472MHD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 4700UF 20% 10V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UVP1A472MHD Specifications

Manufacturer Part NumberUVP1A472MHDManufacturerNichiconCategoryCapacitorsRackageRadial, CanSeriesUVPCapacitance4700μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency2.16A @ 120HzRipple Current - High Frequency2.484A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)
CategoryCapacitorsPackageRadial, CanSeriesUVPCapacitance4700μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency2.16A @ 120HzRipple Current - High Frequency2.484A @ 10kHzImpedance-
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVPCapacitance4700μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency2.16A @ 120HzRipple Current - High Frequency2.484A @ 10kHzImpedance-
Package Series UVP Capacitance 4700µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Ripple Current - Low Frequency Ripple Current - High Frequency Endial, Can UVP 4700µF ±20% 10V -40°C 85°C General Purpose Ripple Current - Low Frequency 2.16A @ 120Hz Ripple Current - High Frequency -484A @ 10kHz Impedance -
SeriesUVPCapacitance $4700\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $10V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency $2.16A @ 120\text{Hz}$ Ripple Current - High Frequency $2.484A @ 10k\text{Hz}$ Impedance-
Capacitance4700μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency2.16A @ 120HzRipple Current - High Frequency2.484A @ 10kHzImpedance-
Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 2.16A @ 120Hz Ripple Current - High Frequency 2.484A @ 10kHz Impedance -
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 2.16A @ 120Hz Ripple Current - High Frequency Lifetime @ Temp. 2000 Hrs @ 85°C 2000 Hrs @ 85°C
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 2.16A @ 120Hz Ripple Current - High Frequency 2.484A @ 10kHz Impedance -
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 2.16A @ 120Hz Ripple Current - High Frequency
Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 2.16A @ 120Hz Ripple Current - High Frequency 2.484A @ 10kHz Impedance -
Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 2.16A @ 120Hz Ripple Current - High Frequency 2.484A @ 10kHz Impedance -
Applications General Purpose Ripple Current - Low Frequency 2.16A @ 120Hz Ripple Current - High Frequency 2.484A @ 10kHz Impedance -
Ripple Current - Low Frequency Ripple Current - High Frequency 2.16A @ 120Hz 2.484A @ 10kHz Impedance -
Ripple Current - High Frequency 2.484A @ 10kHz Impedance -
Impedance -
Lead Spacing 0.295" (7.50mm)
Size / Dimension 0.709" Dia (18.00mm)
Height - Seated (Max) 1.476" (37.50mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

UVP1A472MHD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UVP1A472MHD Payment Methods





















UVP1A472MHD Shipping Methods













If you have any question about UVP1A472MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com