

UVR0J223MHA

Request a Quote

UVR0J223MHA Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVR0J223MHA Specifications

ManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVRCapacitance22000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.000 Hrs @ 85°COperating Temperature900 Hrs @ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.35A @ 100HzRipple Current - High Frequency3.8525A @ 10kHzImpedance-Lad Spacing0.295" (7.50mm)Size / Dimension1.575" (40.00mm)Surface Mount Land Size-Surface Mount Land Size-		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVRCapacitance2000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature900 Hrs @ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.35A @ 100HzRipple Current - High Frequency3.8525A @ 10kHzImpedance-Lad Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.575° (40.00mm)Surface Mount Land Size-	Manufacturer Part Number	UVR0J223MHA
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVRCapacitance22000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency3.35A @ 120HzRipple Current - High Frequency0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-	Manufacturer	Nichicon
PackageRadial, CanSeriesUVRCapacitance22000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.35A @ 120HzRipple Current - High Frequency3.8525A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dinension1.575" (40.00mm)Height - Seated (Max)-Surface Mount Land Size-	Category	Capacitors
SeriesUVRCapacitance22000µFCapacitance±20%Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency3.35A @ 120HzRipple Current - High Frequency3.8525A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-		Aluminum Electrolytic Capacitors
Capacitance22000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency3.35A @ 120HzImpedance-Lad Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.35A @ 120HzBipple Current - High Frequency0.295" (7.50mm)Impedance-Lead Spacing0.709" Dia (18.00mm)Size / Dimension1.575" (40.00mm)Height - Seated (Max)-Surface Mount Land Size-	Series	UVR
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.35A @ 120HzRipple Current - High Frequency3.8525A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-	Capacitance	22000µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.35A @ 120HzRipple Current - High Frequency3.8525A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.35A @ 120HzRipple Current - High Frequency3.8525A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.575" (40.00mm)Height - Seated (Max)-Surface Mount Land Size-	Voltage - Rated	6.3V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.35A @ 120HzRipple Current - High Frequency3.8525A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.35A @ 120HzRipple Current - High Frequency3.8525A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.35A @ 120HzRipple Current - High Frequency3.8525A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency3.35A @ 120HzRipple Current - High Frequency3.8525A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-	Polarization	Polar
InInRipple Current - High Frequency3.8525A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-	Applications	General Purpose
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-	Ripple Current - Low Frequency	3.35A @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-	Ripple Current - High Frequency	3.8525A @ 10kHz
Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-	Impedance	-
Height - Seated (Max) 1.575" (40.00mm) Surface Mount Land Size -	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size -	Size / Dimension	0.709" Dia (18.00mm)
	Height - Seated (Max)	1.575" (40.00mm)
Mounting Type Through Hole	Surface Mount Land Size	-
	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

UVR0J223MHA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVR0J223MHA Payment Methods



UVR0J223MHA Shipping Methods



If you have any question about UVR0J223MHA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com