



UVR1E153MRA Information



For Reference Only

Part Number UVR1E153MRA

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 15000UF 20% 25V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UVR1E153MRA Specifications

Manufacturer Part Number UVR1E153MRA Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UVR Capacitance 15000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Applications Ripple Current - Low Frequency 3.8A @ 120Hz Ripple Current - High Frequency 4.37A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Mututing Type Through Hole		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UVR Capacitance 15000μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.8A @ 120Hz Ripple Current - High Frequency 4.37A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -	Manufacturer Part Number	UVR1E153MRA
PackageRadial, CanSeriesUVRCapacitance15000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.8A @ 120HzRipple Current - High Frequency4.37A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Manufacturer	Nichicon
Package Radial, Can Series UVR Capacitance 15000μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.8A @ 120Hz Ripple Current - High Frequency 4.37A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -	Category	Capacitors
Series UVR Capacitance 15000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.8A @ 120Hz Ripple Current - High Frequency 4.37A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance 15000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.8A @ 120Hz Ripple Current - High Frequency 4.37A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -	Package	Radial, Can
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.8A @ 120Hz Ripple Current - High Frequency 4.37A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -	Series	UVR
Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.8A @ 120Hz Ripple Current - High Frequency 4.37A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -	Capacitance	15000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 4.37A @ 10kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) Surface Mount Land Size -	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.8A @ 120Hz Ripple Current - High Frequency 4.37A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -	Voltage - Rated	25V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 4.37A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) Surface Mount Land Size -40°C ~ 85°C Polar -40°C ~ 85°C Seneral Purpose 3.8A @ 120Hz 4.37A @ 10kHz - - Lead Spacing 0.394" (10.00mm) Surface Mount Land Size	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.8A @ 120Hz Ripple Current - High Frequency 4.37A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 4.37A @ 10kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size General Purpose 3.8A @ 120Hz 4.37A @ 10kHz 1.00mm) 0.866" Dia (22.00mm) 2.047" (52.00mm) -	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 4.37A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -	Applications	General Purpose
Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -	Ripple Current - Low Frequency	3.8A @ 120Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -	Ripple Current - High Frequency	4.37A @ 10kHz
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Impedance	-
Height - Seated (Max) Surface Mount Land Size 2.047" (52.00mm) -	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -	Size / Dimension	0.866" Dia (22.00mm)
	Height - Seated (Max)	2.047" (52.00mm)
Mounting Type Through Hole	Surface Mount Land Size	-
Widuling Type	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

UVR1E153MRA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UVR1E153MRA Payment Methods



















UVR1E153MRA Shipping Methods













If you have any question about UVR1E153MRA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com