



UVR2E221MRA Information



For Reference Only

Part Number UVR2E221MRA

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 220UF 20% 250V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UVR2E221MRA Specifications

Manufacturer Part NumberUVR2E221MRAManufacturerNichiconCategoryCapacitorsPackageRadial, CanSeriesUVRCapacitance220µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency740mA @ 120HzRipple Current - High Frequency1.184A @ 10kHzImpedance-
CategoryCapacitors Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVRCapacitance220μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency740mA @ 120HzRipple Current - High Frequency1.184A @ 10kHz
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVRCapacitance220μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency740mA @ 120HzRipple Current - High Frequency1.184A @ 10kHz
Package Series UVR Capacitance 220µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 1.184A @ 10kHz
SeriesUVRCapacitance220μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency740mA @ 120HzRipple Current - High Frequency1.184A @ 10kHz
Capacitance220μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency740mA @ 120HzRipple Current - High Frequency1.184A @ 10kHz
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 740mA @ 120Hz Ripple Current - High Frequency 1.184A @ 10kHz
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 740mA @ 120Hz Ripple Current - High Frequency 1.184A @ 10kHz
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 740mA @ 120Hz Ripple Current - High Frequency 1.184A @ 10kHz
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 740mA @ 120Hz Ripple Current - High Frequency 1.184A @ 10kHz
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 740mA @ 120Hz Ripple Current - High Frequency 1.184A @ 10kHz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 740mA @ 120Hz Ripple Current - High Frequency 1.184A @ 10kHz
Applications General Purpose Ripple Current - Low Frequency 740mA @ 120Hz Ripple Current - High Frequency 1.184A @ 10kHz
Ripple Current - Low Frequency 740mA @ 120Hz Ripple Current - High Frequency 1.184A @ 10kHz
Ripple Current - High Frequency 1.184A @ 10kHz
Impedance -
Lead Spacing 0.394" (10.00mm)
Size / Dimension 0.787" Dia (20.00mm)
Height - Seated (Max) 1.654" (42.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

UVR2E221MRA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UVR2E221MRA Payment Methods



















UVR2E221MRA Shipping Methods













If you have any question about UVR2E221MRA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com