



#### **UVR2E221MRA Information**



For Reference Only

Part Number UVR2E221MRA

Manufacturer Nichicon
Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 220UF 20% 250V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UVR2E221MRA Specifications**

Category         Capacitors           Package         Radial, Can           Series         UVR           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         740mA @ 120Hz           Ripple Current - High Frequency         1.184A @ 10kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.787" Dia (20.00mm)           Height - Seated (Max)         1.654" (42.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	_	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can UVR Capacitance UVR Capacitance 220µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Lead Spacing Size / Dimension Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Manufacturer Part Number	UVR2E221MRA
Package         Radial, Can           Series         UVR           Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         740mA @ 120Hz           Ripple Current - High Frequency         1.184A @ 10kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.787" Dia (20.00mm)           Height - Seated (Max)         1.654" (42.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	Nichicon
Package         Radial, Can           Series         UVR           Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         740mA @ 120Hz           Ripple Current - High Frequency         1.184A @ 10kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.787" Dia (20.00mm)           Height - Seated (Max)         1.654" (42.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         UVR           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         740mA @ 120Hz           Ripple Current - High Frequency         1.184A @ 10kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.787" Dia (20.00mm)           Height - Seated (Max)         1.654" (42.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance       220μF         Tolerance       ±20%         Voltage - Rated       250V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       2000 Hrs @ 85°C         Operating Temperature       -40°C ~ 85°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       740mA @ 120Hz         Ripple Current - High Frequency       1.184A @ 10kHz         Impedance       -         Lead Spacing       0.394" (10.00mm)         Size / Dimension       0.787" Dia (20.00mm)         Height - Seated (Max)       1.654" (42.00mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 250V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 740mA @ 120Hz  Ripple Current - High Frequency 1.184A @ 10kHz  Impedance - Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.787" Dia (20.00mm)  Height - Seated (Max) 1.654" (42.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	UVR
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.184A @ 120Hz  Impedance  -  Lead Spacing  0.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Polon Hrs @ 85°C  -40°C ~ 85	Capacitance	220μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  740mA @ 120Hz  Ripple Current - High Frequency  1.184A @ 10kHz  Impedance  -  Lead Spacing  0.394" (10.00mm)  Size / Dimension  0.787" Dia (20.00mm)  Height - Seated (Max)  1.654" (42.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.184A @ 120Hz  Impedance  - Lead Spacing  0.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  2000 Hrs @ 85°C  -40°C ~ 85°C  Folarization  901ar  40°C ~ 85°C  901ar  9024  914  915  915  916  916  917  917  918  918  918  918  918  919  919	Voltage - Rated	250V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 740mA @ 120Hz Ripple Current - High Frequency 1.184A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 740mA @ 120Hz  Ripple Current - High Frequency 1.184A @ 10kHz  Impedance -  Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.787" Dia (20.00mm)  Height - Seated (Max) 1.654" (42.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 740mA @ 120Hz Ripple Current - High Frequency 1.184A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 1.184A @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  1.184A @ 10kHz  1.00mm)  0.394" (10.00mm)  0.787" Dia (20.00mm)  1.654" (42.00mm)  Through Hole  Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	740mA @ 120Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	1.184A @ 10kHz
Size / Dimension 0.787" Dia (20.00mm)  Height - Seated (Max) 1.654" (42.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.787" Dia (20.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UVR2E221MRA Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UVR2E221MRA Payment Methods**



















### **UVR2E221MRA Shipping Methods**













If you have any question about UVR2E221MRA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com