

UVR2E470MHD

Request a Quote

UVR2E470MHD Information

	Part Number	UVR2E470MHD	
	Manufacturer	Nichicon	
www.theisenvr.com	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 47UF 20% 250V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVR2E470MHD Specifications

Manufacturer Part NumberUVR2E470MHDManufacturer ANichiconCategoryCapacitorsAtuminum Electrolytic CapacitorsPackageRdial, CanStriesUVRCapacitance4/µFTolerance220%Voltage - Rated250%ESR (Equivalent Series Resistance)-Lifetime Ø Temp.2000 Hrs @ 85°COperating Temperature900 Hrs @ 85°CPolarization900 Hrs @ 85°CApplicationsGeneral PurposeRipple Current - High Frequency300 MA @ 120 HzNipple Current - High Frequency900 Mrs @ 100 HzSize Joinnension1.03°C 7.00mm)Size Joinnension1.03°C 7.00mm)Munting TypeHongh HolePurple Qurent Laws Size Monuting Size	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVRCapacitance47µFTolerance20%Voltage - Rated250VESR (Equivalent Series Resistance)-Derating Temperature2000 Hrs.@ SS°COperating Temperature000 Hrs.@ SS°CPolarizationGeneral PurposeApplicationsGeneral PurposeRippe Current - High Frequency300m A@ 120 HzImpedance-Lead Spacing0.197" (S.00mm)Size / Dimension0.197" (S.00mm)Height - Seated (Max)1.663" (27.00mm)Surface Mount Land Size-Mounting TypeFrougencePackage / CaseMan CanBackage / CaseAgai, Can	Manufacturer Part Number	UVR2E470MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVRCapacitance47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency300mA @ 120HzRipple Current - High Frequency0.197" (5.00mm)Siz / Dimension0.492° Dia (12.50mm)Siz / Dimension0.492° Dia (12.50mm)Siz / Dimension0.492° Dia (12.50mm)Siz / Dimension1.063" (77.00mm)Sirace Mount Land Size-Mounting TypeRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUVRCapacitance47µFTolerance=20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications300mA @ 120HzRipple Current - Low Frequency300mA @ 10HzImpedance-Liad Spacing0.197" (5.00mm)Siz / Dimension0.492" Dia (12.50mm)Siz / Dimension1.063" (72.00mm)Surface Mount Land Size-Mounting TypeFancePackage / CaseStala, Can	Category	Capacitors
SeriesUVRCapacitance47μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGoneral PurposeRipple Current - Low Frequency300mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dinension0.492" Dia (12.50mm)Surface Mount Land Size-Munting TypeThrough HolePoung Type-Starkage / Case-Ring Purpose-Starkage / Case-Starkage / Cas		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage Rated550VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Hugh Frequency480mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePokage / CaseStali, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarPolarApplicationsGeneral PurposeRipple Current - High Frequency300mA @ 120HzMipedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Hight - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	UVR
Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 120HzMipedance-Lead Spacing0.197" (5.00mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	47µF
Constraint - ESR (Equivalent Series Resistance) - ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 300mA @ 120Hz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 120HzBipple Current - High Frequency480mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanCan	Voltage - Rated	250V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 120HzBipple Current - High Frequency480mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 120HzRipple Current - High Frequency480mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 120HzRipple Current - High Frequency480mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency300mA @ 120HzRipple Current - High Frequency480mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In our and a second s	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	300mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	480mA @ 10kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UVR2E470MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVR2E470MHD Payment Methods



UVR2E470MHD Shipping Methods



If you have any question about UVR2E470MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com