



UVR2G101MRD Information



For Reference Only

Part Number UVR2G101MRD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 100UF 20% 400V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UVR2G101MRD Specifications

Manufacturer Part Number UVR2G101MRD Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UVR Capacitance 100μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 120Hz Ripple Current - High Frequency 880mA @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can UVR Capacitance 100µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Ripple Current - High Frequency Somma (0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Manufacturer Part Number	UVR2G101MRD
Package Radial, Can Series UVR Capacitance 100μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 120Hz Ripple Current - High Frequency 880mA @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUVRCapacitance100μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency550mA @ 120HzRipple Current - High Frequency880mA @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.787" Dia (20.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
Series UVR Capacitance 100μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 120Hz Ripple Current - High Frequency 880mA @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 100μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 120Hz Ripple Current - High Frequency 880mA @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 120Hz Ripple Current - High Frequency 880mA @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UVR
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 880mA @ 120Hz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Capacitance	100μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 550mA @ 120Hz Ripple Current - High Frequency 880mA @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 880mA @ 120Hz Ripple Current - High Frequency 880mA @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Voltage - Rated	400V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency S50mA @ 120Hz Ripple Current - High Frequency 880mA @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 120Hz Ripple Current - High Frequency 880mA @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency S50mA @ 120Hz Ripple Current - High Frequency 880mA @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 880mA @ 10kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Case	Ripple Current - Low Frequency	550mA @ 120Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	880mA @ 10kHz
Size / Dimension 0.787" Dia (20.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.787" Dia (20.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
1		Report errors?

UVR2G101MRD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UVR2G101MRD Payment Methods





















UVR2G101MRD Shipping Methods













If you have any question about UVR2G101MRD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com