



UVR2G221MRA Information



For Reference Only

Part Number UVR2G221MRA

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 220UF 20% 400V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UVR2G221MRA Specifications

Manufacturer Part Number UVR2G221MRA Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UVR Capacitance 220µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 750mA @ 120Hz Ripple Current - High Frequency 1.2A @ 10kHz Impedance - Lead Spacing 0.492" (12.50mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole		
Category Capacitors Package Radial, Can Series UVR Capacitance 220µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 750mA @ 120Hz Ripple Current - High Frequency 1.2A @ 10kHz Impedance - Lead Spacing 0.492" (12.50mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole	Manufacturer Part Number	UVR2G221MRA
Aluminum Electrolytic Capacitors Package Radial, Can UVR Capacitance 220µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature - 40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Lead Spacing Mounting Type Aluminum Electrolytic Capacitors Radial, Can UVR 220µF 220µF 220µF 2000 - C 2000 Apov 100 2000 100 2000 100 2000 100 2000 100 2000 100 2000 100 2000 100 2000 100 2000 100 2000 100 2000 100 2000 100 2000 100 2000 1000 10	Manufacturer	Nichicon
Package Radial, Can Series UVR Capacitance 220μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 750mA @ 120Hz Ripple Current - High Frequency 1.2A @ 10kHz Impedance - Lead Spacing 0.492" (12.50mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole	Category	Capacitors
Series UVR Capacitance 220µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 750mA @ 120Hz Ripple Current - High Frequency 1.2A @ 10kHz Impedance - Lead Spacing 0.492" (12.50mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole		Aluminum Electrolytic Capacitors
Capacitance 220μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 750mA @ 120Hz Ripple Current - High Frequency 1.2A @ 10kHz Impedance - Lead Spacing 0.492" (12.50mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole	Package	Radial, Can
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency750mA @ 120HzRipple Current - High Frequency1.2A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	UVR
Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency750mA @ 120HzRipple Current - High Frequency1.2A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	220μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 750mA @ 120Hz Ripple Current - High Frequency 1.2A @ 10kHz Impedance Lead Spacing 0.492" (12.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type - Through Hole	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 750mA @ 120Hz Ripple Current - High Frequency 1.2A @ 10kHz Impedance - Lead Spacing 0.492" (12.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 2000 Hrs @ 85°C -40°C ~ 85°C -40°C ~ 85°C -40°C ~ 85°C -6000	Voltage - Rated	400V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 750mA @ 120Hz Ripple Current - High Frequency 1.2A @ 10kHz Impedance - Lead Spacing 0.492" (12.50mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type Through Hole	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 750mA @ 120Hz Ripple Current - High Frequency 1.2A @ 10kHz Impedance - Lead Spacing 0.492" (12.50mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 1.2A @ 10kHz Impedance - Lead Spacing 0.492" (12.50mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type General Purpose 750mA @ 120Hz 1.2A @ 10kHz 1.2A @	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 1.2A @ 10kHz Impedance Lead Spacing 0.492" (12.50mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.492" (12.50mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type 1.2A @ 10kHz - Commonstruction 1.2A @ 10kHz - Through Hole	Applications	General Purpose
Impedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	750mA @ 120Hz
Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	1.2A @ 10kHz
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type 2.047" (52.00mm) - Through Hole	Lead Spacing	0.492" (12.50mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	0.984" Dia (25.00mm)
Mounting Type Through Hole	Height - Seated (Max)	2.047" (52.00mm)
	Surface Mount Land Size	-
D 1 1 0	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

UVR2G221MRA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UVR2G221MRA Payment Methods



















UVR2G221MRA Shipping Methods













If you have any question about UVR2G221MRA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com