



#### **UVR2G3R3MPA Information**



For Reference Only

Part Number UVR2G3R3MPA

Manufacturer Nichicon Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 3.3UF 20% 400V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UVR2G3R3MPA** Specifications

Manufacturer Part Number         UVR2G3R3MPA           Manufacturer         Nichicon           Category         Capacitors           Package         Radial, Can           Series         UVR           Capacitance         3.3µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         55mA @ 120Hz           Ripple Current - High Frequency         88mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.551" (14.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole		
Category         Capacitors           Package         Radial, Can           Series         UVR           Capacitance         3.3 µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         55mA @ 120Hz           Ripple Current - High Frequency         88mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.551" (14.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Manufacturer Part Number	UVR2G3R3MPA
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVRCapacitance3.3μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency88mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	Nichicon
Package         Radial, Can           Series         UVR           Capacitance         3.3µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         55mA @ 120Hz           Ripple Current - High Frequency         88mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.551" (14.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Category	Capacitors
Series         UVR           Capacitance         3.3µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         55mA @ 120Hz           Ripple Current - High Frequency         88mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.551" (14.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole		Aluminum Electrolytic Capacitors
Capacitance3.3μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency88mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency88mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	UVR
Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency88mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	3.3µF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  S5mA @ 120Hz  Ripple Current - High Frequency  88mA @ 10kHz  Impedance  Lead Spacing  0.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  - Through Hole	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  S5mA @ 120Hz  Ripple Current - High Frequency  88mA @ 10kHz  Impedance  -  Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.394" Dia (10.00mm)  Height - Seated (Max)  O.551" (14.00mm)  Surface Mount Land Size  -  Mounting Type  Through Hole	Voltage - Rated	400V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency S5mA @ 120Hz Ripple Current - High Frequency 88mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 55mA @ 120Hz  Ripple Current - High Frequency 88mA @ 10kHz  Impedance -  Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.551" (14.00mm)  Surface Mount Land Size -  Mounting Type Through Hole	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  88mA @ 10kHz  Impedance	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  88mA @ 10kHz  Impedance  Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.394" Dia (10.00mm)  Height - Seated (Max)  0.551" (14.00mm)  Surface Mount Land Size  Mounting Type  Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	55mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	88mA @ 10kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  0.551" (14.00mm)  - Through Hole	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole	Height - Seated (Max)	0.551" (14.00mm)
	Surface Mount Land Size	-
	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

#### **UVR2G3R3MPA** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UVR2G3R3MPA Payment Methods**



















### **UVR2G3R3MPA Shipping Methods**













If you have any question about UVR2G3R3MPA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com