

UVY0J683MRD

UVY0J683MRD Information



Part Number	UVY0J683MRD	
Manufacturer	Nichicon	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP ALUM 68000UF 20% 6.3V RADIAL	
Package	Radial, Can	
	For the pricing/inventory/lead time, please contact	
us		
Website: https://www.heisener.com		
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVY0J683MRD Specifications

ManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVYCapacitance68000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature9core 20°CPolarizationGeneral PurposeApplicationsGonz AlumentaRipple Current - High Frequency3.505A @ 10kHzImpedance-Lead Spacing0.984" Dia (25.00mm)Size / Dimension9.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUVYCapacitance68000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.5305A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	UVY0J683MRD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVYCapacitance68000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency3.5305A @ 10kHzRipple Current - High Frequency0.492° (12.50mm)Size / Dimension0.984° Dia (25.00mm)Height - Seated (Max)2.047° (52.00mm)Surface Mount Land Size-Package / CaseKadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUVYCapacitance68000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency3.5305A @ 10kHzRiple Current - High Frequency0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseKalial, Can	Category	Capacitors
SeriesUVYCapacitance68000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.07A @ 120HzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.5305A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolariPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.07A @ 120HzImpedance-Lead Spacing0.984° Dia (25.00mm)Size / Dimension0.984° Dia (25.00mm)Height - Seated (Max)2.047″ (52.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UVY
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.07A @ 120HzBipple Current - High Frequency3.0305A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Capacitance	68000µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.07A @ 120HzBipple Current - High Frequency3.5305A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.07A @ 120HzRipple Current - High Frequency3.5305A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	6.3V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.07A @ 120Hz Ripple Current - High Frequency 3.5305A @ 10kHz Impedance - Lead Spacing 0.492" (12.50mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Finough Hole Package / Case Kadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.07A @ 120HzRipple Current - High Frequency3.5305A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.07A @ 120HzRipple Current - High Frequency3.5305A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency3.07A @ 120HzRipple Current - High Frequency3.5305A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency3.5305A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	3.07A @ 120Hz
Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	3.5305A @ 10kHz
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.492" (12.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
·	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UVY0J683MRD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVY0J683MRD Payment Methods



UVY0J683MRD Shipping Methods



If you have any question about UVY0J683MRD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com