

UVY2A100MDD

UVY2A100MDD Information

www.heisener.com	Part Number Manufacturer Category Description Package	Capacitors Aluminum Electrolytic Capacitors CAP ALUM 10UF 20% 100V RADIAL Radial, Can	
		For the pricing/inventory/lead time, please contact us	E149222
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVY2A100MDD Specifications

Manufacturer Part NumberUVY2A100MDDManufacturer AndNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVYCapacitanceJupfTolerance200%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime Temp.1000 Hrs @105°COperating Temperature55°C ~ 105°CPolarization6eneral PurposeApplicationsSom A @ 120HzRipple Current - High Frequency000 A @ 120HzLided Spacing007° (200mm)Size / Dimension0.97° (200mm)Highel Seated (Max)0.92° (12.50mm)Surface Mount Land Size-Mounting TypeHorugh HelePackage CaseAnigh HelePolarige Case-Surface Mount Land Size-Surface Mount Land Size-Polarige Case-Polarige Case-Surface Mount Land Size-Polarige Case-Polarige Case-Polarie Case <td< th=""><th>-</th><th></th></td<>	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVYCapacitance10µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency50mA @ 100Hrs @ 100H	Manufacturer Part Number	UVY2A100MDD
AckageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVYCapacitance10µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 10kHzImpedance.Lead Spacing0.197" Dia (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size.Hounting TypeRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUVYCapacitance10µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Hog Frequency50mA @ 100HzImpedance.Liad Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Size / Dimension0.492° (12.50mm)Surface Mount Land Size.Mounting TypeFrequencyRackage / CaseRadial, Can	Category	Capacitors
SeriesUVYCapacitance10µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 100HzImpedance-Lead Spacing0.079° (2.00mm)Size / Dimension0.197" Dia (5.00mm)Bight - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalial, Can		Aluminum Electrolytic Capacitors
Capacitance10µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency100m A @ 10kHzImpedance-Size / Dimension0.197° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Sirafe Mount Land Size-Mounting TypeThrough HolePackage / CaseRatia, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseRatial Can	Series	UVY
Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 120HzImpedance-Lead Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.492° (12.50mm)Surface Mount Land Size-Hounting TypeFnought CancelPackage / CaseRatial, Can	Capacitance	10µF
EVE-ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 120HzNipedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeRadial, Can	Voltage - Rated	100V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 120HzBipple Current - High Frequency100mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 120HzRipple Current - High Frequency100mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 120HzRipple Current - High Frequency100mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency50mA @ 120HzRipple Current - High Frequency100mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the frequency100mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	50mA @ 120Hz
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	100mA @ 10kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors ²	Package / Case	Radial, Can
		Report errors?

UVY2A100MDD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVY2A100MDD Payment Methods



UVY2A100MDD Shipping Methods



If you have any question about UVY2A100MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com