

UVY2A102MHD

UVY2A102MHD Information

www.helsener.com	Part Number Manufacturer Category Description Package	Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1000UF 20% 100V RADIAL Radial, Can	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVY2A102MHD Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVYCapacitance1000µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeRipple Current - High Frequency960mA @ 120HzImpedance-Lied Spacing0.295° (7.50mm)Size / Dimension0.295° (7.50mm)Height - Seated (Max)1.476° (37.50mm)Surface Mount Land Size-Package / CaseKaila, Can	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVYCapacitance1000µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.104A @ 10kHzImpedance-Lied Spacing0.295° (7.50mm)Size / Dimension1.476° (37.50mm)Height - Seated (Max)1.476° (37.50mm)Surface Mount Land Size-Package / CaseKadia, Can	Manufacturer Part Number	UVY2A102MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVYCapacitance1000µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency960mA @ 120HzRipple Current - High Frequency1.104A @ 10kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.476° (37.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUVYCapacitance1000μFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency960mA @ 120HzRiple Current - High Frequency1.104A @ 10kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.476° (37.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesUVYCapacitance1000µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzInpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.476° (37.50mm)Surface Mount Land Size-Package / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzInpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia , Can	Package	Radial, Can
Tolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.476° (37.50mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	UVY
Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.476" (37.50mm)Height - Seated (Max)1.476" (37.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	1000µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.476" (37.50mm)Height - Seated (Max)1.476" (37.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.476" (37.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	100V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzRipple Current - High Frequency1.104A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.476" (37.50mm)Surface Mount Land Size-Package / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzRipple Current - High Frequency1.104A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.476" (37.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzRipple Current - High Frequency1.104A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.476" (37.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency960mA @ 120HzRipple Current - High Frequency1.104A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.476" (37.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency1.104A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.476" (37.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.476" (37.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	960mA @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.476" (37.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.104A @ 10kHz
Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.476" (37.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.476" (37.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.476" (37.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UVY2A102MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVY2A102MHD Payment Methods



UVY2A102MHD Shipping Methods



If you have any question about UVY2A102MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com