

UVY2V331MRD

equest a Quote

UVY2V331MRD Information

ww.s.elsoner.com	Part Number	UVY2V331MRD
	Manufacturer	Nichicon
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 330UF 20% 350V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVY2V331MRD Specifications

ManufacturerNichiconCapacitorsCapacitorsPackageRadial, CanPackageRadial, CanSeriesUVYCapacitance30µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - Low Frequency816.5mA @ 10kHzImpedance-Lied Spacing0.492° (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUVYCapacitance30µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency816.5mA @ 10kHzImpedance-Lead Spacing0.984" Dia (25.00mm)Siz / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseKadia, Can	Manufacturer Part Number	UVY2V331MRD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVYCapacitance330µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency816.5mA @ 10kHzRipple Current - High Frequency816.5mA @ 10kHzImpedance-Lead Spacing0.984" Dia (25.00mm)Size / Dimension2.047" (52.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUVYCapacitance330µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency816.5mA @ 10kHzRiple Current - High Frequency816.5mA @ 10kHzImpedance-Lead Spacing0.492° (12.50mm)Size / Dimension2.047" (52.00mm)Strace Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUVYCapacitance330µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency710mA @ 120HzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Bight - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated550VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency710mA @ 120HzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarrPolarApplicationsGeneral PurposeRipple Current - Low Frequency710mA @ 120HzRipple Current - High Frequency816.5mA @ 10kHzImpedance-Lead Spacing0.984" Dia (25.00mm)Size / Dimension2.047" (52.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UVY
Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency710mA @ 120HzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	330µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency710mA @ 120HzBipple Current - High Frequency816.5mA @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency710mA @ 120HzRipple Current - High Frequency816.5mA @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	350V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency710mA @ 120HzRipple Current - High Frequency816.5mA @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency710mA @ 120HzRipple Current - High Frequency816.5mA @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency710mA @ 120HzRipple Current - High Frequency816.5mA @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency710mA @ 120HzRipple Current - High Frequency816.5mA @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the second secon	Applications	General Purpose
Impedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	710mA @ 120Hz
Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	816.5mA @ 10kHz
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.492" (12.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UVY2V331MRD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVY2V331MRD Payment Methods



UVY2V331MRD Shipping Methods



If you have any question about UVY2V331MRD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com