

UVZ1A682MHH

Request a Quote

UVZ1A682MHH Information

w whelse her.com	Part Number	UVZ1A682MHH	
	Manufacturer	Nichicon	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 6800UF 20% 10V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVZ1A682MHH Specifications

Manufacturer Part Number UVZ1 A682MHH Manufacturer Nichicon Category Capacitors Atuminum Electrolytic Capacitors Atuminum Electrolytic Capacitors Package Radial, Can Series UVZ Capacitance 6800µF Tolerance ±20% Voltage - Rated 10V SSR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization General Purpose Applications General Purpose Rippe Current - Low Frequency 1.57A @ 120Hz Impedance - Lead Spacing 0.295° (7.50mm) Size / Dimension 0.630° Dia (16.00mm) Height - Seated (Max) 0.630° Dia (16.00mm) Size / Dimension - Mounting Type Through Hole Package / Case Radia (Can	•	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVZCapacitance6800µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.51X @ 100HrzImpedance0.295°(7.50mm)Liad Spacing0.630° Dia (16.00mm)Size / Dimension1.063°(27.00mm)Hight - Seated (Max)1.063°(27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can	Manufacturer Part Number	UVZ1A682MHH
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesUVZCapacitance6800µFTolerance±20%Voltage - Rated0VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplications555°A @ 10kHzRipple Current - Low Frequency1.57A @ 120HzRipple Current - High Frequency0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Size / Dimension1.063° (27.00mm)Height - Seated (Max)1.063° (27.00mm)Surface Mount Land Size-Pounting TypeRadia, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUVZCapacitance6800µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationGeneral PurposeApplications1.57A @ 120HzRipple Current - High Frequency1.8055A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.063" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUVZCapacitance6800µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Hugh Frequency1.57A @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseSaial, Can		Aluminum Electrolytic Capacitors
Capacitance6800µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime Temp.1000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.57A @ 100 HrzInpedance-Size / Dimension0.295° (7.50mn)Size / Dimension0.630° Dia (1.600mn)Sizer / Dimension1.663° (27.00mn)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.57A @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseRatial, Can	Series	UVZ
Voltage - RatedIOVESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.57A @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.063° (27.00mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseRational	Capacitance	6800µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.57A @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.063° (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.57A @ 120HzRipple Current - High Frequency1.8055A @ 10kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.063° (27.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	Voltage - Rated	10V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.57A @ 120HzRipple Current - High Frequency1.8055A @ 10kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.063° (27.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.57A @ 120HzRipple Current - High Frequency1.8055A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.57A @ 120HzRipple Current - High Frequency1.8055A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency1.57A @ 120HzRipple Current - High Frequency1.8055A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the field	Applications	General Purpose
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.57A @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.8055A @ 10kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can
		Report errors?

UVZ1A682MHH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVZ1A682MHH Payment Methods



UVZ1A682MHH Shipping Methods



If you have any question about UVZ1A682MHH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com