

UVZ1C332MHH

Request a Quote

UVZ1C332MHH Information

w.w.helsener.com	Part Number	UVZ1C332MHH	
	Manufacturer	Nichicon	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 3300UF 20% 16V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVZ1C332MHH Specifications

ManufacturerNichiconCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUVZCapacitance3300µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzRipple Current - High Frequency3.455A @ 10kHzImpedance-Lied Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUVZCapacitance3300µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzRipple Current - High Frequency0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	UVZ1C332MHH
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVZCapacitance3300µFTolerance±20%Voltage - Rated6VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzRipple Current - High Frequency0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension1.063" (27.00mm)Surface Mount Land Size-Mounting TypeRatial, CanPackage / CaseRatial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUVZCapacitance300µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplications.117A @ 120HzRipple Current - Low Frequency.13455A @ 10kHzImpedance-Lad Spacing0.197" (5.00mm)Siz / Dimension.1063" (27.00mm)Siz / Dimension.1063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesUVZCapacitance3300µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzInpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance3300µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRidil, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	UVZ
Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	3300µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzRipple Current - High Frequency1.3455A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	16V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzRipple Current - High Frequency1.3455A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzRipple Current - High Frequency1.3455A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzRipple Current - High Frequency1.3455A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency1.17A @ 120HzRipple Current - High Frequency1.3455A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.17A @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.3455A @ 10kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UVZ1C332MHH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVZ1C332MHH Payment Methods



UVZ1C332MHH Shipping Methods



If you have any question about UVZ1C332MHH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com