



## **UVZ1J331MPD Information**



For Reference Only

Part Number UVZ1J331MPD

Manufacturer Nichicon
Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 330UF 20% 63V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UVZ1J331MPD Specifications**

Manufacturer Part Number         UVZIJ331MPD           Manufacturer         Nichicon           Category         Capacitors           Package         Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         UVZ           Capacitance         330µF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           ESR (Equivalent Series Resistance)         1000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         General Purpose           Ripple Current - Low Frequency         510mA @ 120Hz           Ripple Current - High Frequency         765mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         UVZ           Capacitance         330μF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         510mA @ 120Hz           Ripple Current - High Frequency         765mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	UVZ1J331MPD
Aluminum Electrolytic Capacitors  Package Radial, Can  UVZ  Capacitance 330µF  Tolerance ±20%  Voltage - Rated 63V  ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C  Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Tespenance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size - Mounting Type Package / Case Radial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUVZCapacitance330µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency510mA @ 120HzRipple Current - High Frequency765mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
Series         UVZ           Capacitance         330µF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         510mA @ 120Hz           Ripple Current - High Frequency         765mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance330μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency510mA @ 120HzRipple Current - High Frequency765mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 63V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 510mA @ 120Hz Ripple Current - High Frequency 765mA @ 10kHz  Impedance - Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.866" (22.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	UVZ
Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency510mA @ 120HzRipple Current - High Frequency765mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	330μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  1000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  510mA @ 120Hz  Ripple Current - High Frequency  765mA @ 10kHz  Impedance  -  Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.394" Dia (10.00mm)  Height - Seated (Max)  0.866" (22.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -55°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  765mA @ 120Hz  Impedance  Lead Spacing  0.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  1000 Hrs @ 105°C  -55°C ~ 105°C  Ronard  Foliar  Ogeneral Purpose  Foliar  General Purpose  1000 Hrs @ 120Hz  Foliar  Ogeneral Purpose  1000 Hrs @ 120Hz  Foliar  Ogeneral Purpose  1000 Hrs @ 105°C  Foliar  Ogeneral Purpose  1000 Hrs @ 105°  Foliar  Ogeneral Purpose  1000 Hrs @ 105°  Foliar  Ogeneral Purpose  1000 Hrs @ 105°  Foliar  Ogeneral Purpose  1000 Hrs @ 100 Hrs @ 100 Hrs  Foliar  Ogeneral Purpose  1000 Hrs @ 1000 Hrs  Foliar  Ogeneral Purpose  1000 Hrs @ 10	Voltage - Rated	63V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency S10mA @ 120Hz Ripple Current - High Frequency 765mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 510mA @ 120Hz  Ripple Current - High Frequency 765mA @ 10kHz  Impedance -  Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.866" (22.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
Applications  General Purpose  Ripple Current - Low Frequency  Frequency  Fipple Current - High Frequency  Fre	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  765mA @ 10kHz  Impedance  - Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.394" Dia (10.00mm)  Height - Seated (Max)  0.866" (22.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Polarization	Polar
Ripple Current - High Frequency  Impedance  Lead Spacing  O.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  765mA @ 10kHz  - 0.197" (5.00mm)  0.394" Dia (10.00mm)  0.394" Dia (10.00mm)  Through Hole  Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	510mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	765mA @ 10kHz
Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.866" (22.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UVZ1J331MPD** Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UVZ1J331MPD Payment Methods**



















### **UVZ1J331MPD Shipping Methods**













If you have any question about UVZ1J331MPD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com