



UVZ1V471MPH Information



For Reference Only

Part Number UVZ1V471MPH

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 470UF 20% 35V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UVZ1V471MPH Specifications

Category Capacitors Package Radial, Can Series UVZ Capacitance 470µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 460mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole		
Category Capacitors Package Radial, Can Series UVZ Capacitance 470μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 460mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	UVZ1V471MPH
Package Radial, Can Series UVZ Capacitance 470μF Tolerance ±20% Voltage - Rated 35 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 460mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
Package Radial, Can Series UVZ Capacitance 470μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 460mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UVZ Capacitance 470µF Tolerance ±20% Voltage - Rated 35 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 460mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 470μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 460mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 460mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UVZ
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 105°C -55°C ~ 105°C Roman General Purpose 460mA @ 120Hz - 1000 Hrs @ 105°C - 1000 Hrs @ 105° - 1000 Hrs @ 105° - 1000 Hrs @ 105° - 1000 Hrs @ 1000 Hrs @ 1000 Hrs @ 1000 Hrs elles Helles Hel	Capacitance	470μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 460mA @ 120Hz Ripple Current - High Frequency Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 105°C -55°C ~ 105°C -640mA @ 120Hz -740mm -740m	Voltage - Rated	35V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 460mA @ 120Hz Ripple Current - High Frequency - Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 460mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 460mA @ 120Hz Ripple Current - High Frequency	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency 460mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing O.197" (5.00mm) Size / Dimension O.394" Dia (10.00mm) Height - Seated (Max) O.689" (17.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	460mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.689" (17.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UVZ1V471MPH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UVZ1V471MPH Payment Methods



















UVZ1V471MPH Shipping Methods













If you have any question about UVZ1V471MPH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com