

UVZ2D010MED

UVZ2D010MED Information

www.ħeišener.com	Part Number	UVZ2D010MED	
	Manufacturer	Nichicon	
	Category	Capacitors Aluminum Electrolytic Capacitors	1000
	Description	CAP ALUM 1UF 20% 200V RADIAL	- 57,426-)
	Package	Radial, Can	「吉が乱し
		For the pricing/inventory/lead time, please contact us	Ш 74774
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVZ2D010MED Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVZCapacitanceµFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperaturee40°C ~ 105°CPolarizationGeneral PurposeRipple Current - High Frequency16mA @ 120HzRipple Current - High Frequency0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Size / Dimension0.449°C (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaial, Can	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageUVZCapacitanceIµFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency16mA @ 120HzRipple Current - High Frequency25.6mA @ 10kHzImpedance-Lied Spacing0.098° (2.50mm)Size / Dimension0.492° (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	UVZ2D010MED
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVZCapacitanceμFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency25.6mA @ 10kHzRipple Current - High Frequency25.6mA @ 10kHzSize / Dimension0.248° Dia (6.30mm)Size / Dimension0.492° (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUVZCapacitance1µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency16mA @ 120HzRipple Current - High Frequency25.6mA @ 10kHzImpedance-Lad Spacing0.098° (2.50mm)Size / Dimension0.448° Dia (6.30mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUVZCapacitanceμFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16mA @ 120HzRipple Current - High Frequency25.6mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can		Aluminum Electrolytic Capacitors
CapacitanceμFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16mA @ 120HzImpedance-Lead Spacing0.098° (2.50mm)Size / Dimension0.248° Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Poung TypeThrough HolePackage / CaseKalia, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	UVZ
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRatial, Can	Capacitance	1μF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16mA @ 120HzBipple Current - High Frequency25.6mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16mA @ 120HzBipple Current - High Frequency25.6mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	200V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16mA @ 120HzRipple Current - High Frequency25.6mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16mA @ 120HzRipple Current - High Frequency25.6mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency16mA @ 120HzRipple Current - High Frequency25.6mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency16mA @ 120HzRipple Current - High Frequency25.6mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	16mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	25.6mA @ 10kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UVZ2D010MED Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVZ2D010MED Payment Methods



UVZ2D010MED Shipping Methods



If you have any question about UVZ2D010MED, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com