

UVZ2D4R7MPH

UVZ2D4R7MPH Information

| www.fieisener.com | Part Number Manufacturer Category Description Package | Capacitors Aluminum Electrolytic Capacitors CAP ALUM 4.7UF 20% 200V RADIAL Radial, Can | |
|--------------------|---|--|-----------------|
| For Reference Only | | For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVZ2D4R7MPH Specifications

| ManufacturerNichiconCapacitorsCapacitorsAtuminum Electrolytic CapacitorsPackageRadial, CanSeriesUVZCapacitance4.7µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - Low Frequency62.4mA @ 10kHzRipple Current - High Frequency0.315" Dia (8.00mm)Size / Dimension0.315" Dia (8.00mm)Size / Dimension5.12" (13.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | | |
|--|------------------------------------|----------------------------------|
| CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUVZCapacitance4.7µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency62.4mA @ 10kHzRipple Current - High Frequency0.315" Dia (8.00mm)Size / Dimension0.315" Dia (8.00mm)Size / Dimension0.512" (13.00mm)Surface Mount Land Size-Mounting TypeFacial CanPackage / CaseRadial, Can | Manufacturer Part Number | UVZ2D4R7MPH |
| Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVZCapacitance4.7µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency39mA @ 120HzRipple Current - High Frequency62.4mA @ 10kHzSize / Dimension0.315" Dia (8.00mm)Size / Dimension0.512" (13.00mm)Surface Mount Land Size-Mounting TypeFacage / CasePackage / CaseRadial, Can | Manufacturer | Nichicon |
| PackageRadial, CanSeriesUVZCapacitance4.7µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency39mA @ 120HzRipple Current - High Frequency0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Size / Dimension0.512" (13.00mm)Surface Mount Land Size-Mounting TypeRadial, Can | Category | Capacitors |
| SeriesUVZCapacitance4.7μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzRipple Current - High Frequency62.4mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Surface Mount Land Size-Monting TypeThrough HolePackage / CaseRatial, Can | | Aluminum Electrolytic Capacitors |
| Capacitance4.7µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseKaial, Can | Package | Radial, Can |
| Tolerance±0%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzBipple Current - High Frequency0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Size / Dimension0.512" (13.00mm)Surface Mount Land Size-Package / CaseRatial, Can | Series | UVZ |
| Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzBipple Current - High Frequency62.4mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Package / CaseRatial, Can | Capacitance | 4.7µF |
| ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzBipple Current - High Frequency62.4mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Package / CaseRadial, Can | Tolerance | ±20% |
| Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzBipple Current - High Frequency62.4mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Voltage - Rated | 200V |
| Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzBipple Current - High Frequency62.4mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max).512" (13.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can | ESR (Equivalent Series Resistance) | - |
| PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzBipple Current - High Frequency62.4mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Lifetime @ Temp. | 1000 Hrs @ 105°C |
| ApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzRipple Current - High Frequency62.4mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Operating Temperature | -40°C ~ 105°C |
| Ripple Current - Low Frequency39mA @ 120HzRipple Current - High Frequency62.4mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Polarization | Polar |
| InInRipple Current - High Frequency62.4mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Applications | General Purpose |
| In restriction-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Ripple Current - Low Frequency | 39mA @ 120Hz |
| Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Ripple Current - High Frequency | 62.4mA @ 10kHz |
| Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Impedance | - |
| Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Lead Spacing | 0.138" (3.50mm) |
| Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Size / Dimension | 0.315" Dia (8.00mm) |
| Mounting TypeThrough HolePackage / CaseRadial, Can | Height - Seated (Max) | 0.512" (13.00mm) |
| Package / Case Radial, Can | Surface Mount Land Size | - |
| | Mounting Type | Through Hole |
| Report errors? | Package / Case | Radial, Can |
| | | Report errors? |

UVZ2D4R7MPH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVZ2D4R7MPH Payment Methods



UVZ2D4R7MPH Shipping Methods



If you have any question about UVZ2D4R7MPH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com