

UVZ2V470MHH

Request a Quote

UVZ2V470MHH Information

www.hetsener.com	Part Number	UVZ2V470MHH	
	Manufacturer	Nichicon	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 47UF 20% 350V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UVZ2V470MHH Specifications

ManufacturerNichiconCagacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUVZCapacitance47µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - Low Frequency32mA @ 10kHzImpedance-Lied Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.456° (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVZCapacitance47µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency432mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	UVZ2V470MHH
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUVZCapacitance47µFTolerance±20%Voltage - RatedSoVESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency270mA @ 120HzRipple Current - High Frequency0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.456° (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUVZCapacitance47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency270mA @ 120HzRiple Current - High Frequency0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.456° (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesUVZCapacitance47µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency432mA @ 10kHzInpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.456° (37.00mm)Surface Mount Land Size-Package / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency270mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)-Surface Mount Land Size-Pokage / CaseKaila, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency270mA @ 120HzRipple Current - High Frequency0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.456° (37.00mm)Surface Mount Land Size-Pokage / CaseRidia, Can	Series	UVZ
Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency270mA @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.456° (37.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Capacitance	47µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency270mA @ 120HzBipple Current - High Frequency432mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency270mA @ 120HzRipple Current - High Frequency432mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can	Voltage - Rated	350V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency270mA @ 120HzRipple Current - High Frequency432mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency270mA @ 120HzRipple Current - High Frequency432mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency270mA @ 120HzRipple Current - High Frequency432mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency270mA @ 120HzRipple Current - High Frequency432mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency432mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	270mA @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	432mA @ 10kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.456" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.456" (37.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UVZ2V470MHH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UVZ2V470MHH Payment Methods



UVZ2V470MHH Shipping Methods



If you have any question about UVZ2V470MHH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com