



## V110A8T200BS Information

Heisener.com

Part Number V110A8T200BS Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

**Description** CONVERTER MOD DC/DC 8V 200W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# V110A8T200BS Specifications

Manufacturer Part Number         V110A8T200BS           Manufacturer         Vicor Corporation           Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         Maxi           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         154V           Voltage - Output 1         8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         25A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -40°C ~ 100°C           Efficiency         87.7%           Mounting Type         Through Hole		
Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         Maxi           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         154V           Voltage - Output 1         8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         25A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -40°C ~ 100°C           Efficiency         87.7%           Mounting Type         Through Hole	Manufacturer Part Number	V110A8T200BS
DC DC Converters           Package         Full Brick           Series         Maxi           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         154V           Voltage - Output 1         8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         25A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -40°C ~ 100°C           Efficiency         87.7%           Mounting Type         Through Hole	Manufacturer	Vicor Corporation
Package         Full Brick           Series         Maxi           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         154V           Voltage - Output 1         8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         25A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -40°C ~ 100°C           Efficiency         87.7%           Mounting Type         Through Hole	Category	Power Supplies - Board Mount
Series         Maxi           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         154V           Voltage - Output 1         8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         25A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -40°C ~ 100°C           Efficiency         87.7%           Mounting Type         Through Hole		DC DC Converters
Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         154V           Voltage - Output 1         8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         25A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -40°C ~ 100°C           Efficiency         87.7%           Mounting Type         Through Hole	Package	Full Brick
Number of Outputs       1         Voltage - Input (Min)       66V         Voltage - Input (Max)       154V         Voltage - Output 1       8V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       25A         Power (Watts)       200W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OVP, UVLO         Operating Temperature       -40°C ~ 100°C         Efficiency       87.7%         Mounting Type       Through Hole	Series	Maxi
Voltage - Input (Min)         66V           Voltage - Input (Max)         154V           Voltage - Output 1         8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         25A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -40°C ~ 100°C           Efficiency         87.7%           Mounting Type         Through Hole	Туре	Isolated Module
Voltage - Input (Max)         154V           Voltage - Output 1         8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         25A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -40°C ~ 100°C           Efficiency         87.7%           Mounting Type         Through Hole	Number of Outputs	1
Voltage - Output 1         8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         25A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -40°C ~ 100°C           Efficiency         87.7%           Mounting Type         Through Hole	Voltage - Input (Min)	66V
Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       25A         Power (Watts)       200W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OVP, UVLO         Operating Temperature       -40°C ~ 100°C         Efficiency       87.7%         Mounting Type       Through Hole	Voltage - Input (Max)	154V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  Features  OVP, UVLO  Operating Temperature  Efficiency  Mounting Type	Voltage - Output 1	8V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OVP, UVLO  Operating Temperature  -40°C ~ 100°C  Efficiency  87.7%  Mounting Type  Through Hole	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  200W  Voltage - Isolation  Applications  ITE (Commercial)  Features  OVP, UVLO  Operating Temperature  -40°C ~ 100°C  Efficiency  87.7%  Mounting Type  Through Hole	Voltage - Output 3	-
Power (Watts) $200W$ Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)Features $OVP$ , $UVLO$ Operating Temperature $-40^{\circ}C \sim 100^{\circ}C$ Efficiency $87.7\%$ Mounting TypeThrough Hole	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOVP, UVLOOperating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Efficiency $87.7\%$ Mounting TypeThrough Hole	Current - Output (Max)	25A
ApplicationsITE (Commercial)FeaturesOVP, UVLOOperating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Efficiency $87.7\%$ Mounting TypeThrough Hole	Power (Watts)	200W
Features OVP, UVLO Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Efficiency 87.7% Mounting Type Through Hole	Voltage - Isolation	3kV (3000V)
Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Efficiency $87.7\%$ Mounting Type Through Hole	Applications	ITE (Commercial)
Efficiency 87.7%  Mounting Type Through Hole	Features	OVP, UVLO
Mounting Type Through Hole	Operating Temperature	-40°C ~ 100°C
	Efficiency	87.7%
D 1 / / / / D 1 / / D 1 / / D 1 / D	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 2.20" W x 0.54" H (116.8mm x 55.9mm x 13.7mm)	Size / Dimension	4.60" L x 2.20" W x 0.54" H (116.8mm x 55.9mm x 13.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

#### V110A8T200BS Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## V110A8T200BS Payment Methods



















## V110A8T200BS Shipping Methods













If you have any question about V110A8T200BS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com