



# V150A36C400BG2 Information



For Reference Only

Part Number V150A36C400BG2
Manufacturer Vicor Corporation

**Category** Power Supplies - Board Mount

DC DC Converters

**Description** CONVERTER MOD DC/DC 36V 400W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# V150A36C400BG2 Specifications

Manufacturer         Vicor Corporation           Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         Maxi           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         100V           Voltage - Input (Max)         200V           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         11.11A           Power (Watts)         400W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -20°C ~ 100°C           Efficiency         89.3%           Mounting Type         Through Hole           Package / Case         Full Brick           Size / Dimension         4.60" L x 2.20" W x 0.62" H (116.8mm x 55.9mm x 15.7mm)	Manufacturer Part Number	V150A36C400BG2
Package         Full Brick           Series         Maxi           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         100V           Voltage - Input (Max)         200V           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         11.11A           Power (Watts)         400W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -20°C ~ 100°C           Efficiency         89.3%           Mounting Type         Through Hole           Package / Case         Full Brick	Manufacturer	Vicor Corporation
Package         Full Brick           Series         Maxi           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         100V           Voltage - Input (Max)         200V           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         11.11A           Power (Watts)         400W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -20°C ~ 100°C           Efficiency         89.3%           Mounting Type         Through Hole           Package / Case         Full Brick	Category	Power Supplies - Board Mount
Series         Maxi           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         100V           Voltage - Input (Max)         200V           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         11.11A           Power (Watts)         400W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -20°C ~ 100°C           Efficiency         89.3%           Mounting Type         Through Hole           Package / Case         Full Brick		DC DC Converters
Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         100V           Voltage - Input (Max)         200V           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         11.11A           Power (Watts)         400W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -20°C ~ 100°C           Efficiency         89.3%           Mounting Type         Through Hole           Package / Case         Full Brick	Package	Full Brick
Number of Outputs       1         Voltage - Input (Min)       100V         Voltage - Input (Max)       200V         Voltage - Output 1       36V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       11.11A         Power (Watts)       400W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OVP, UVLO         Operating Temperature       -20°C ~ 100°C         Efficiency       89.3%         Mounting Type       Through Hole         Package / Case       Full Brick	Series	Maxi
Voltage - Input (Max)         200V           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         11.11A           Power (Watts)         400W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -20°C ~ 100°C           Efficiency         89.3%           Mounting Type         Through Hole           Package / Case         Full Brick	Туре	Isolated Module
Voltage - Input (Max)         200V           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         11.11A           Power (Watts)         400W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -20°C ~ 100°C           Efficiency         89.3%           Mounting Type         Through Hole           Package / Case         Full Brick	Number of Outputs	1
Voltage - Output 1       36V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       11.11A         Power (Watts)       400W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OVP, UVLO         Operating Temperature       -20°C ~ 100°C         Efficiency       89.3%         Mounting Type       Through Hole         Package / Case       Full Brick	Voltage - Input (Min)	100V
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OVP, UVLO Operating Temperature Efficiency 89.3% Mounting Type Through Hole Package / Case  - Output 3 - Commercial - Current - Output (Max) - Current - Outpu	Voltage - Input (Max)	200V
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OVP, UVLO  Operating Temperature  Efficiency  89.3%  Mounting Type  Package / Case  Full Brick	Voltage - Output 1	36V
Voltage - Output 4  Current - Output (Max)  11.11A  Power (Watts)  400W  Voltage - Isolation  3kV (3000V)  Applications  ITE (Commercial)  Features  OVP, UVLO  Operating Temperature  -20°C ~ 100°C  Efficiency  89.3%  Mounting Type  Through Hole  Package / Case  Full Brick	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  400W  Voltage - Isolation  3kV (3000V)  Applications  ITE (Commercial)  Features  OVP, UVLO  Operating Temperature  -20°C ~ 100°C  Efficiency  89.3%  Mounting Type  Through Hole  Package / Case  Full Brick	Voltage - Output 3	-
Power (Watts) 400W  Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OVP, UVLO  Operating Temperature -20°C ~ 100°C  Efficiency 89.3%  Mounting Type Through Hole  Package / Case Full Brick	Voltage - Output 4	-
Voltage - Isolation3kV (3000V)ApplicationsITE (Commercial)FeaturesOVP, UVLOOperating Temperature-20°C ~ 100°CEfficiency89.3%Mounting TypeThrough HolePackage / CaseFull Brick	Current - Output (Max)	11.11A
Applications ITE (Commercial)  Features OVP, UVLO  Operating Temperature -20°C ~ 100°C  Efficiency 89.3%  Mounting Type Through Hole  Package / Case Full Brick	Power (Watts)	400W
Features OVP, UVLO Operating Temperature -20°C ~ 100°C  Efficiency 89.3%  Mounting Type Through Hole Package / Case Full Brick	Voltage - Isolation	3kV (3000V)
Operating Temperature -20°C ~ 100°C  Efficiency 89.3%  Mounting Type Through Hole  Package / Case Full Brick	Applications	ITE (Commercial)
Efficiency 89.3%  Mounting Type Through Hole  Package / Case Full Brick	Features	OVP, UVLO
Mounting Type Through Hole Package / Case Full Brick	Operating Temperature	-20°C ~ 100°C
Package / Case Full Brick	Efficiency	89.3%
	Mounting Type	Through Hole
Size / Dimension 4.60" L x 2.20" W x 0.62" H (116.8mm x 55.9mm x 15.7mm)	Package / Case	Full Brick
	Size / Dimension	4.60" L x 2.20" W x 0.62" H (116.8mm x 55.9mm x 15.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

#### V150A36C400BG2 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# V150A36C400BG2 Payment Methods


































If you have any question about V150A36C400BG2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com