



#### V23030C2014A106 Information

Heisener.com

**Part Number** V23030C2014A106

Manufacturer TE Connectivity Potter & Brumfield Relays

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE 6PDT 2A 60V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## V23030C2014A106 Specifications

Manufacturer Part NumberV23030C2014A106ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPackage-SeriesV23030, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current14.6mACoil Voltage60VDCContact Form6PDT (6 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)45 VDCTurn Off Voltage (Min)-Operate Time8msRelease Time2ms		
Category  Relays  Signal Relays, Up to 2 Amps  Package  - Series  V23030, AXICOM  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  14.6mA  Coil Voltage  60VDC  Contact Form  6PDT (6 Form C)  Contact Rating (Current)  2A  Switching Voltage  250VAC, 250VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  8ms	Manufacturer Part Number	V23030C2014A106
Package - Series V23030, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 14.6mA Coil Voltage 60VDC Contact Form 6PDT (6 Form C) Contact Rating (Current) 2A Switching Voltage (Max) 45 VDC Turn Off Voltage (Min) - Operate Time 8ms	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - V23030, AXICOM  Relay Type General Purpose Coil Type Non Latching Coil Current 14.6mA Coil Voltage 60VDC Contact Form 6PDT (6 Form C) Contact Rating (Current) 2A Switching Voltage Max) 45 VDC Turn Off Voltage (Min) - Operate Time 8ms	Category	Relays
Series V23030, AXICOM  Relay Type General Purpose  Coil Type Non Latching  Coil Current 14.6mA  Coil Voltage 60VDC  Contact Form 6PDT (6 Form C)  Contact Rating (Current) 2A  Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) 45 VDC  Turn Off Voltage (Min) -  Operate Time 8ms		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current14.6mACoil Voltage60VDCContact Form6PDT (6 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)45 VDCTurn Off Voltage (Min)-Operate Time8ms	Package	-
Coil Type Non Latching  Coil Current 14.6mA  Coil Voltage 60VDC  Contact Form 6PDT (6 Form C)  Contact Rating (Current) 2A  Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) 45 VDC  Turn Off Voltage (Min) -  Operate Time 8ms	Series	V23030, AXICOM
Coil Current 14.6mA Coil Voltage 60VDC Contact Form 6PDT (6 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 45 VDC Turn Off Voltage (Min) - Operate Time 8ms	Relay Type	General Purpose
Coil Voltage 60VDC Contact Form 6PDT (6 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 45 VDC Turn Off Voltage (Min) - Operate Time 8ms	Coil Type	Non Latching
Contact Form 6PDT (6 Form C)  Contact Rating (Current) 2A  Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) 45 VDC  Turn Off Voltage (Min) -  Operate Time 8ms	Coil Current	14.6mA
Contact Rating (Current)  Switching Voltage  250VAC, 250VDC - Max  Turn On Voltage (Max)  45 VDC  Turn Off Voltage (Min)  Operate Time  8ms	Coil Voltage	60VDC
Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 45 VDC Turn Off Voltage (Min) - Operate Time 8ms	Contact Form	6PDT (6 Form C)
Turn On Voltage (Max) 45 VDC Turn Off Voltage (Min) - Operate Time 8ms	Contact Rating (Current)	2A
Turn Off Voltage (Min) - Operate Time 8ms	Switching Voltage	250VAC, 250VDC - Max
Operate Time 8ms	Turn On Voltage (Max)	45 VDC
	Turn Off Voltage (Min)	-
Release Time 2ms	Operate Time	8ms
	Release Time	2ms
Features -	Features	-
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

#### **V23030C2014A106 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### V23030C2014A106 Payment Methods



















### V23030C2014A106 Shipping Methods













If you have any question about V23030C2014A106, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com