



### **V23050-A1110-A533 Information**



For Reference Only

Part Number V23050-A1110-A533

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY SAFETY 6PST 8A 110V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## V23050-A1110-A533 Specifications

Manufacturer Part Number         V23050-A1110-A533           Manufacturer         TE Connectivity Potter & Brumfield Relays           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         SR6, SCHRACK           Relay Type         Safety           Coil Type         Non Latching           Coil Current         10.9mA           Coil Voltage         110VDC           Contact Form         6PST (3 Form A, 3 Form B)           Contact Rating (Current)         8A           Switching Voltage         400VAC - Max           Turn On Voltage (Max)         82.5 VDC           Turn Off Voltage (Min)         11 VDC           Operate Time         -           Release Time         -           Features         -           Mounting Type         Through Hole           Termination Style         PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesSR6, SCHRACKRelay TypeSafetyCoil TypeNon LatchingCoil Current10.9mACoil Voltage110VDCContact Form6PST (3 Form A, 3 Form B)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)11 VDCOperate Time-Release Time-Features-Mounting TypeThrough Hole	Manufacturer Part Number	V23050-A1110-A533
Package         -           Series         SR6, SCHRACK           Relay Type         Safety           Coil Type         Non Latching           Coil Current         10.9mA           Coil Voltage         110VDC           Contact Form         6PST (3 Form A, 3 Form B)           Contact Rating (Current)         8A           Switching Voltage         400VAC - Max           Turn On Voltage (Max)         82.5 VDC           Turn Off Voltage (Min)         11 VDC           Operate Time         -           Release Time         -           Features         -           Mounting Type         Through Hole	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesSR6, SCHRACKRelay TypeSafetyCoil TypeNon LatchingCoil Current10.9mACoil Voltage110VDCContact Form6PST (3 Form A, 3 Form B)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)11 VDCOperate Time-Release Time-Features-Mounting TypeThrough Hole	Category	Relays
SeriesSR6, SCHRACKRelay TypeSafetyCoil TypeNon LatchingCoil Current10.9mACoil Voltage110VDCContact Form6PST (3 Form A, 3 Form B)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)11 VDCOperate Time-Release Time-Features-Mounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay TypeSafetyCoil TypeNon LatchingCoil Current10.9mACoil Voltage110VDCContact Form6PST (3 Form A, 3 Form B)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)11 VDCOperate Time-Release Time-Features-Mounting TypeThrough Hole	Package	-
Coil Type Non Latching Coil Current 10.9mA Coil Voltage 110VDC Contact Form 6PST (3 Form A, 3 Form B) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time - Release Time - Features - Mounting Type Through Hole	Series	SR6, SCHRACK
Coil Current Coil Voltage 110VDC Contact Form 6PST (3 Form A, 3 Form B) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time - Release Time - Features Mounting Type Through Hole	Relay Type	Safety
Coil Voltage 110VDC Contact Form 6PST (3 Form A, 3 Form B) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time - Release Time - Features - Mounting Type Through Hole	Coil Type	Non Latching
Contact Form 6PST (3 Form A, 3 Form B)  Contact Rating (Current) 8A  Switching Voltage 400VAC - Max  Turn On Voltage (Max) 82.5 VDC  Turn Off Voltage (Min) 11 VDC  Operate Time -  Release Time -  Features -  Mounting Type Through Hole	Coil Current	10.9mA
Contact Rating (Current)  Switching Voltage  400VAC - Max  Turn On Voltage (Max)  82.5 VDC  Turn Off Voltage (Min)  11 VDC  Operate Time  - Release Time  - Wounting Type  Through Hole	Coil Voltage	110VDC
Switching Voltage 400VAC - Max  Turn On Voltage (Max) 82.5 VDC  Turn Off Voltage (Min) 11 VDC  Operate Time -  Release Time -  Features -  Mounting Type Through Hole	Contact Form	6PST (3 Form A, 3 Form B)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  -  Features  Mounting Type  82.5 VDC  11 VDC  -  Through Hole	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  Release Time  -  Features  -  Mounting Type  Through Hole	Switching Voltage	400VAC - Max
Operate Time - Release Time - Company - Compan	Turn On Voltage (Max)	82.5 VDC
Release Time - Features - Mounting Type Through Hole	Turn Off Voltage (Min)	11 VDC
Features - Through Hole	Operate Time	-
Mounting Type Through Hole	Release Time	-
	Features	-
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

#### **V23050-A1110-A533 Guarantees**



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## V23050-A1110-A533 Payment Methods



















## V23050-A1110-A533 Shipping Methods













If you have any question about V23050-A1110-A533, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com