

#### V23057-A0002-A201 Information

Part Number V23057-A0002-A201

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 8A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## V23057-A0002-A201 Specifications

Manufacturer Part NumberV23057-A0002-A201ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesV23057, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.3mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8 VDCTurn Off Voltage (Min)1.2 VDCOperate Time7msRelease Time3msFeatures-Mounting TypeThrough Hole		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         V23057, SCHRACK           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         36.3mA           Coil Voltage         12VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         8A           Switching Voltage         400VAC - Max           Turn On Voltage (Max)         8 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         7ms           Release Time         3ms           Features         -	Manufacturer Part Number	V23057-A0002-A201
Package - Series V23057, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 36.3mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 8 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 7ms Release Time 3ms Features -	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesV23057, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.3mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8 VDCTurn Off Voltage (Min)1.2 VDCOperate Time7msRelease Time3msFeatures-	Category	Relays
Series         V23057, SCHRACK           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         36.3mA           Coil Voltage         12VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         8A           Switching Voltage         400VAC - Max           Turn On Voltage (Max)         8 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         7ms           Release Time         3ms           Features         -		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.3mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8 VDCTurn Off Voltage (Min)1.2 VDCOperate Time7msRelease Time3msFeatures-	Package	-
Coil Type Non Latching Coil Current 36.3mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 8 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 7ms Release Time 3ms Features -	Series	V23057, SCHRACK
Coil Current36.3mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8 VDCTurn Off Voltage (Min)1.2 VDCOperate Time7msRelease Time3msFeatures-	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 8 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 7ms Release Time 3ms Features -	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current) 8A  Switching Voltage 400VAC - Max  Turn On Voltage (Max) 8 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 7ms  Release Time 3ms  Features -	Coil Current	36.3mA
Contact Rating (Current)  Switching Voltage  400VAC - Max  Turn On Voltage (Max)  8 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  7ms  Release Time  3ms  Features  -	Coil Voltage	12VDC
Switching Voltage 400VAC - Max  Turn On Voltage (Max) 8 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 7ms  Release Time 3ms  Features -	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  3ms  Features  -	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  Release Time  3ms  Features  -	Switching Voltage	400VAC - Max
Operate Time 7ms Release Time 3ms Features -	Turn On Voltage (Max)	8 VDC
Release Time 3ms Features -	Turn Off Voltage (Min)	1.2 VDC
Features -	Operate Time	7ms
	Release Time	3ms
Mounting Type Through Hole	Features	-
	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

### V23057-A0002-A201 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### V23057-A0002-A201 Payment Methods



















## V23057-A0002-A201 Shipping Methods













If you have any question about V23057-A0002-A201, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com