

V23057A 23A101 Information

Heisener.com

V23057A 23A101 Part Number

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 5A 60V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









V23057A 23A101 Specifications

Manufacturer Part Number V23057A 23A101 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series V23057, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 60VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 40 VDC Turn Off Voltage (Min) 6 VDC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesV23057, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage60VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)40 VDCTurn Off Voltage (Min)6 VDCOperate Time7msRelease Time3msFeatures-Mounting TypeThrough Hole	Manufacturer Part Number	V23057A 23A101
Package - Series V23057, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 60VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 40 VDC Turn Off Voltage (Min) 6 VDC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - V23057, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 60VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 40 VDC Turn Off Voltage (Min) 6 VDC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole	Category	Relays
SeriesV23057, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage60VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)40 VDCTurn Off Voltage (Min)6 VDCOperate Time7msRelease Time3msFeatures-Mounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage60VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)40 VDCTurn Off Voltage (Min)6 VDCOperate Time7msRelease Time3msFeatures-Mounting TypeThrough Hole	Package	-
Coil Type	Series	V23057, SCHRACK
Coil Current 8.3mA Coil Voltage 60VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 40 VDC Turn Off Voltage (Min) 6 VDC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage60VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)40 VDCTurn Off Voltage (Min)6 VDCOperate Time7msRelease Time3msFeatures-Mounting TypeThrough Hole	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 40 VDC Turn Off Voltage (Min) 6 VDC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole	Coil Current	8.3mA
Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 40 VDC Turn Off Voltage (Min) 6 VDC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole	Coil Voltage	60VDC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 40 VDC Turn Off Voltage (Min) 6 VDC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole	Contact Rating (Current)	5A
Turn Off Voltage (Min) 6 VDC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole	Switching Voltage	400VAC - Max
Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole	Turn On Voltage (Max)	40 VDC
Release Time 3ms Features - Mounting Type Through Hole	Turn Off Voltage (Min)	6 VDC
Features - Through Hole	Operate Time	7ms
Mounting Type Through Hole	Release Time	3ms
	Features	-
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

V23057A 23A101 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

V23057A 23A101 Payment Methods



















V23057A 23A101 Shipping Methods













If you have any question about V23057A 23A101, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com