



#### **V23061A1002A502 Information**



For Reference Only

Part Number V23061A1002A502

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GENERAL PURPOSE SPST 8A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## V23061A1002A502 Specifications

Manufacturer Part NumberV23061A1002A502ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMSR, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current42.4mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough Hole		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMSR, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current42.4mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class A, Sealed - Fully	Manufacturer Part Number	V23061A1002A502
Package - Series MSR, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 42.4mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class A, Sealed - Fully	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series MSR, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 42.4mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class A, Sealed - Fully	Category	Relays
Series MSR, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 42.4mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class A, Sealed - Fully		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current42.4mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class A, Sealed - Fully	Package	-
Coil Type Non Latching Coil Current 42.4mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class A, Sealed - Fully	Series	MSR, SCHRACK
Coil Current 42.4mA Coil Voltage 5VDC  Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class A, Sealed - Fully	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class A, Sealed - Fully	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 8A  Switching Voltage 400VAC - Max  Turn On Voltage (Max) 3.4 VDC  Turn Off Voltage (Min) 0.5 VDC  Operate Time 10ms  Release Time 5ms  Features Insulation - Class A, Sealed - Fully	Coil Current	42.4mA
Contact Rating (Current)  8A  Switching Voltage 400VAC - Max  Turn On Voltage (Max) 3.4 VDC  Turn Off Voltage (Min) 0.5 VDC  Operate Time 10ms  Release Time 5ms  Features Insulation - Class A, Sealed - Fully	Coil Voltage	5VDC
Switching Voltage 400VAC - Max  Turn On Voltage (Max) 3.4 VDC  Turn Off Voltage (Min) 0.5 VDC  Operate Time 10ms  Release Time 5ms  Features Insulation - Class A, Sealed - Fully	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class A, Sealed - Fully	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class A, Sealed - Fully	Switching Voltage	400VAC - Max
Operate Time 10ms Release Time 5ms Features Insulation - Class A, Sealed - Fully	Turn On Voltage (Max)	3.4 VDC
Release Time 5ms Features Insulation - Class A, Sealed - Fully	Turn Off Voltage (Min)	0.5 VDC
Features Insulation - Class A, Sealed - Fully	Operate Time	10ms
·	Release Time	5ms
Mounting Type Through Hole	Features	Insulation - Class A, Sealed - Fully
Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

### **V23061A1002A502** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## V23061A1002A502 Payment Methods



















### V23061A1002A502 Shipping Methods













If you have any question about V23061A1002A502, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com