



#### **V23079C1102B301 Information**



For Reference Only

Part Number V23079C1102B301

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GENERAL PURPOSE DPDT 2A 6V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## V23079C1102B301 Specifications

Manufacturer Part NumberV23079C1102B301ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPackage-SeriesV23079, AXICOMRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current11.7mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeThrough Hole		
Category         Relays           Signal Relays, Up to 2 Amps           Package         -           Series         V23079, AXICOM           Relay Type         General Purpose           Coil Type         Latching, Single Coil           Coil Current         11.7mA           Coil Voltage         6VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         2A           Switching Voltage         250VAC, 220VDC - Max           Turn On Voltage (Max)         4.5 VDC           Turn Off Voltage (Min)         -           Operate Time         4ms           Release Time         4ms           Features         -	Manufacturer Part Number	V23079C1102B301
Package - Series V23079, AXICOM Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 11.7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features -	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package         -           Series         V23079, AXICOM           Relay Type         General Purpose           Coil Type         Latching, Single Coil           Coil Current         11.7mA           Coil Voltage         6VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         2A           Switching Voltage         250VAC, 220VDC - Max           Turn On Voltage (Max)         4.5 VDC           Turn Off Voltage (Min)         -           Operate Time         4ms           Release Time         4ms           Features         -	Category	Relays
Series V23079, AXICOM Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 11.7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features -		Signal Relays, Up to 2 Amps
Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 11.7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features -	Package	-
Coil Type Latching, Single Coil Coil Current 11.7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features -	Series	V23079, AXICOM
Coil Current 11.7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features -	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features -	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 250VAC, 220VDC - Max  Turn On Voltage (Max) 4.5 VDC  Turn Off Voltage (Min) -  Operate Time 4ms  Release Time 4ms  Features -	Coil Current	11.7mA
Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  4.5 VDC  Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  -	Coil Voltage	6VDC
Switching Voltage 250VAC, 220VDC - Max  Turn On Voltage (Max) 4.5 VDC  Turn Off Voltage (Min) - Operate Time 4ms  Release Time 4ms  Features -	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  4.5 VDC  Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  -	Contact Rating (Current)	2A
Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features -	Switching Voltage	250VAC, 220VDC - Max
Operate Time 4ms Release Time 4ms Features -	Turn On Voltage (Max)	4.5 VDC
Release Time 4ms Features -	Turn Off Voltage (Min)	-
Features -	Operate Time	4ms
	Release Time	4ms
Mounting Type Through Hole	Features	-
	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

#### **V23079C1102B301 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### V23079C1102B301 Payment Methods





















### V23079C1102B301 Shipping Methods













If you have any question about V23079C1102B301, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com