



V23100V6003A112 Information

Heisener.com

V23100V6003A112 Part Number

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Signal Relays, Up to 2 Amps

RELAY REED DPST 350MA 24V **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









V23100V6003A112 Specifications

Manufacturer Part Number V23100V6003A112 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Signal Relays, Up to 2 Amps Package - Series V23100-V6, AXICOM Relay Type Reed Coil Type Non Latching Coil Current 6.2mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 350mA Switching Voltage 24VDC - Nom Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesV23100-V6, AXICOMRelay TypeReedCoil TypeNon LatchingCoil Current6.2mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)350mASwitching Voltage24VDC - NomTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	V23100V6003A112
Package-SeriesV23100-V6, AXICOMRelay TypeReedCoil TypeNon LatchingCoil Current6.2mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)350mASwitching Voltage24VDC - NomTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series V23100-V6, AXICOM Relay Type Reed Coil Type Non Latching Coil Current 6.2mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 350mA Switching Voltage 24VDC - Nom Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series V23100-V6, AXICOM Relay Type Reed Coil Type Non Latching Coil Current 6.2mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 350mA Switching Voltage 24VDC - Nom Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current6.2mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)350mASwitching Voltage24VDC - NomTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 6.2mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 350mA Switching Voltage 24VDC - Nom Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Series	V23100-V6, AXICOM
Coil Current Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 350mA Switching Voltage 24VDC - Nom Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time Release Time - Features Mounting Type Through Hole Termination Style 6.2mA 6.2mB 6.2mA 6.2mB 6.2mA 6.2mB 6.2mA 6.2mB 6.2mB 6.2mA 6.2mB 6.2m	Relay Type	Reed
Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 350mA Switching Voltage 24VDC - Nom Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 350mA Switching Voltage 24VDC - Nom Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Coil Current	6.2mA
Contact Rating (Current) Switching Voltage 24VDC - Nom Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time Release Time - Release Time Features Mounting Type Through Hole Termination Style 350mA 350mA 350mA 24VDC - Nom - Nom Turn Off Voltage (Max) - Turn Off Voltage (Min) - Turn Off Volt	Coil Voltage	24VDC
Switching Voltage 24VDC - Nom Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time - Retures - Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	350mA
Turn Off Voltage (Min) Operate Time Release Time - Features Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	24VDC - Nom
Operate Time Release Time	Turn On Voltage (Max)	-
Release Time	Turn Off Voltage (Min)	-
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	-
Mounting Type Through Hole Termination Style PC Pin	Release Time	-
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

V23100V6003A112 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

V23100V6003A112 Payment Methods



















V23100V6003A112 Shipping Methods













If you have any question about V23100V6003A112, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com