



V23101D 107A301 Information



For Reference Only

Part Number V23101D 107A301

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 3A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









V23101D 107A301 Specifications

Manufacturer Part Number V23101D 107A301 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series V23101, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 8.6mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 125VAC, 120VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin		
Category Relays Power Relays, Over 2 Amps Package - Series V23101, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 8.6mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 125VAC, 120VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Manufacturer Part Number	V23101D 107A301
Package - Series V23101, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 8.6mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 125VAC, 120VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series V23101, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 8.6mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 125VAC, 120VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series V23101, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 8.6mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 125VAC, 120VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.6mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)3ASwitching Voltage125VAC, 120VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 8.6mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 125VAC, 120VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Series	V23101, AXICOM
Coil Current8.6mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)3ASwitching Voltage125VAC, 120VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 125VAC, 120VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 125 VAC, 120 VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Current	8.6mA
Contact Rating (Current) Switching Voltage 125VAC, 120VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	24VDC
Switching Voltage 125VAC, 120VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	3A
Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	125VAC, 120VDC - Max
Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	18 VDC
Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	7ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	-
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

V23101D 107A301 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

V23101D 107A301 Payment Methods



















V23101D 107A301 Shipping Methods













If you have any question about V23101D 107A301, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com