



V24A5H300BN Information

Heisener.com

V24A5H300BN Part Number Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 5V 300W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









V24A5H300BN Specifications

Manufacturer Part Number Manufacturer Vicor Corporation Vicor Corporation Power Supplies - Board Mount DC DC Converters Package Full Brick Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) Voltage - Input (Max) Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Fower (Watts) Voltage - Isolation AbV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature Efficiency 84.4%		
Power Supplies - Board Mount	Manufacturer Part Number	V24A5H300BN
Package Full Brick Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 60A Power (Watts) 300W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C	Manufacturer	Vicor Corporation
Package Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 60A Power (Watts) 300W Voltage - Isolation 3kV (3000V) Applications Features OVP, UVLO Operating Temperature	Category	Power Supplies - Board Mount
Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 60A Power (Watts) 300W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 60A Power (Watts) 300W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 60A Power (Watts) 300W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C	Series	Maxi
Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 60A Power (Watts) 300W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C	Туре	Isolated Module
Voltage - Input (Max) 36V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 60A Power (Watts) 300W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C	Number of Outputs	1
Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 60A Power (Watts) 300W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C	Voltage - Input (Min)	18V
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C	Voltage - Input (Max)	36V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C	Voltage - Output 1	5V
Voltage - Output 4-Current - Output (Max) $60A$ Power (Watts) $300W$ Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)Features OVP , $UVLO$ Operating Temperature $-40^{\circ}C \sim 100^{\circ}C$	Voltage - Output 2	-
Current - Output (Max) $60A$ Power (Watts) $300W$ Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)Features $OVP, UVLO$ Operating Temperature $-40^{\circ}C \sim 100^{\circ}C$	Voltage - Output 3	
Power (Watts) $300W$ Voltage - Isolation $3kV$ ($3000V$)ApplicationsITE (Commercial)Features OVP , $UVLO$ Operating Temperature $-40^{\circ}C \sim 100^{\circ}C$	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOVP, UVLOOperating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$	Current - Output (Max)	60A
Applications ITE (Commercial) Features OVP, UVLO Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$	Power (Watts)	300W
Features OVP, UVLO Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$	Voltage - Isolation	3kV (3000V)
Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$	Applications	ITE (Commercial)
	Features	OVP, UVLO
Efficiency 84.4%	Operating Temperature	-40°C ~ 100°C
	Efficiency	84.4%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 2.20" W x 0.54" H (116.8mm x 55.9mm x 13.7mm)	Size / Dimension	4.60" L x 2.20" W x 0.54" H (116.8mm x 55.9mm x 13.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

V24A5H300BN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

V24A5H300BN Payment Methods



















V24A5H300BN Shipping Methods













If you have any question about V24A5H300BN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com