



#### V24B15E200BN2 Information

Heisener.com

V24B15E200BN2 Part Number Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

**Description** CONVERTER MOD DC/DC 15V 200W

Package 9-DIP Module

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# V24B15E200BN2 Specifications

Manufacturer         Vicor Corporation           Category         Power Supplies - Board Mount           DC DC Converters           Package         9-DIP Module           Series         MINI           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         15V           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -10°C - 100°C           Efficiency         86.6%           Mounting Type         Through Hole           Package / Case         9-DIP Module           Size / Dimension         2.28" L x 2.20" W x 0.50" H (57.9mm x 55.9mm x 12.7mm)	Manufacturer Part Number	V24B15E200BN2
DC DC Converters	Manufacturer	Vicor Corporation
Package         9-DIP Module           Series         MINI           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -10°C ~ 100°C           Efficiency         86.6%           Mounting Type         Through Hole           Package / Case         9-DIP Module	Category	Power Supplies - Board Mount
Series         MINI           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -10°C ~ 100°C           Efficiency         86.6%           Mounting Type         Through Hole           Package / Case         9-DIP Module		DC DC Converters
Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -10°C ~ 100°C           Efficiency         86.6%           Mounting Type         Through Hole           Package / Case         9-DIP Module	Package	9-DIP Module
Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -10°C ~ 100°C           Efficiency         86.6%           Mounting Type         Through Hole           Package / Case         9-DIP Module	Series	MINI
Voltage - Input (Min)         18V           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -10°C ~ 100°C           Efficiency         86.6%           Mounting Type         Through Hole           Package / Case         9-DIP Module	Туре	Isolated Module
Voltage - Input (Max)         36V           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -10°C ~ 100°C           Efficiency         86.6%           Mounting Type         Through Hole           Package / Case         9-DIP Module	Number of Outputs	1
Voltage - Output 1       15V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       13.33A         Power (Watts)       200W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OVP, UVLO         Operating Temperature       -10°C ~ 100°C         Efficiency       86.6%         Mounting Type       Through Hole         Package / Case       9-DIP Module	Voltage - Input (Min)	18V
Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         200W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OVP, UVLO           Operating Temperature         -10°C ~ 100°C           Efficiency         86.6%           Mounting Type         Through Hole           Package / Case         9-DIP Module	Voltage - Input (Max)	36V
Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       13.33A         Power (Watts)       200W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OVP, UVLO         Operating Temperature       -10°C ~ 100°C         Efficiency       86.6%         Mounting Type       Through Hole         Package / Case       9-DIP Module	Voltage - Output 1	15V
Voltage - Output 4       -         Current - Output (Max)       13.33A         Power (Watts)       200W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OVP, UVLO         Operating Temperature       -10°C ~ 100°C         Efficiency       86.6%         Mounting Type       Through Hole         Package / Case       9-DIP Module	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  200W  Voltage - Isolation  3kV (3000V)  Applications  ITE (Commercial)  Features  OVP, UVLO  Operating Temperature  -10°C ~ 100°C  Efficiency  86.6%  Mounting Type  Through Hole  Package / Case  9-DIP Module	Voltage - Output 3	-
Power (Watts)  Voltage - Isolation  3kV (3000V)  Applications  ITE (Commercial)  Features  OVP, UVLO  Operating Temperature  -10°C ~ 100°C  Efficiency  86.6%  Mounting Type  Through Hole  Package / Case  9-DIP Module	Voltage - Output 4	-
Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OVP, UVLO  Operating Temperature -10°C ~ 100°C  Efficiency 86.6%  Mounting Type Through Hole  Package / Case 9-DIP Module	Current - Output (Max)	13.33A
Applications ITE (Commercial)  Features OVP, UVLO  Operating Temperature -10°C ~ 100°C  Efficiency 86.6%  Mounting Type Through Hole  Package / Case 9-DIP Module	Power (Watts)	200W
Features OVP, UVLO Operating Temperature -10°C ~ 100°C  Efficiency 86.6%  Mounting Type Through Hole Package / Case 9-DIP Module	Voltage - Isolation	3kV (3000V)
Operating Temperature -10°C ~ 100°C  Efficiency 86.6%  Mounting Type Through Hole  Package / Case 9-DIP Module	Applications	ITE (Commercial)
Efficiency 86.6%  Mounting Type Through Hole  Package / Case 9-DIP Module	Features	OVP, UVLO
Mounting Type Through Hole Package / Case 9-DIP Module	Operating Temperature	-10°C ~ 100°C
Package / Case 9-DIP Module	Efficiency	86.6%
	Mounting Type	Through Hole
Size / Dimension 2.28" L x 2.20" W x 0.50" H (57.9mm x 55.9mm x 12.7mm)	Package / Case	9-DIP Module
	Size / Dimension	2.28" L x 2.20" W x 0.50" H (57.9mm x 55.9mm x 12.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

#### V24B15E200BN2 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## V24B15E200BN2 Payment Methods





















## V24B15E200BN2 Shipping Methods













If you have any question about V24B15E200BN2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com