



V24C15T150BL3 Information

Heisener.com

Part Number V24C15T150BL3

Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 15V 150W

Package Quarter Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









V24C15T150BL3 Specifications

Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Quarter Brick Series MICRO Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 89.3% Mounting Type Through Hole	Manufacturer Part Number	V24C15T150BL3
DC DC Converters	Manufacturer	Vicor Corporation
Package Quarter Brick Series MICRO Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 89.3%	Category	Power Supplies - Board Mount
Series MICRO Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 89.3%		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 89.3%	Package	Quarter Brick
Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 89.3%	Series	MICRO
Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 89.3%	Туре	Isolated Module
Voltage - Input (Max) 36V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 89.3%	Number of Outputs	1
Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 89.3%	Voltage - Input (Min)	18V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 150W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 89.3%	Voltage - Input (Max)	36V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 89.3%	Voltage - Output 1	15V
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 89.3%	Voltage - Output 2	-
Current - Output (Max) 10A Power (Watts) 150W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -40°C ~ 100°C Efficiency 89.3%	Voltage - Output 3	-
Power (Watts) $150W$ Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)Features $OVP, UVLO$ Operating Temperature $-40^{\circ}C \sim 100^{\circ}C$ Efficiency 89.3%	Voltage - Output 4	-
Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOVP, UVLOOperating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Efficiency 89.3%	Current - Output (Max)	10A
ApplicationsITE (Commercial)FeaturesOVP, UVLOOperating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Efficiency 89.3%	Power (Watts)	150W
Features OVP, UVLO Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Efficiency 89.3%	Voltage - Isolation	3kV (3000V)
Operating Temperature -40°C ~ 100°C Efficiency 89.3%	Applications	ITE (Commercial)
Efficiency 89.3%	Features	OVP, UVLO
	Operating Temperature	-40°C ~ 100°C
Mounting Type Through Hole	Efficiency	89.3%
	Mounting Type	Through Hole
Package / Case Quarter Brick	Package / Case	Quarter Brick
Size / Dimension 2.28" L x 1.45" W x 0.62" H (57.9mm x 36.8mm x 15.7mm)	Size / Dimension	2.28" L x 1.45" W x 0.62" H (57.9mm x 36.8mm x 15.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

V24C15T150BL3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

V24C15T150BL3 Payment Methods



















V24C15T150BL3 Shipping Methods













If you have any question about V24C15T150BL3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com