



V375A36T500B Information



For Reference Only

Part Number V375A36T500B
Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 36V 500W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









V375A36T500B Specifications

Manufacturer Part Number Manufacturer Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series Maxi Type Isolated Module Number of Outputs I Voltage - Input (Min) Voltage - Input (Max) Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Voltage - Isolation Applications ITE (Commercial) Features OVP, UVLO Operating Temperature	
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.89A Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
DC DC Converters Package Full Brick Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.89A Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Package Full Brick Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.89A Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.89A Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.89A Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.89A Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.89A Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Voltage - Input (Max) 425V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.89A Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.89A Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.89A Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.89A Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Voltage - Output 4 - Current - Output (Max) 13.89A Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OVP, UVLO	
Power (Watts) 500W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	
Applications ITE (Commercial) Features OVP, UVLO	
Features OVP, UVLO	
Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$	
Efficiency 88%	
Mounting Type Through Hole	
Package / Case Full Brick	
Size / Dimension 4.60" L x 2.20" W x 0.54" H (116.8mm x 55.9mm x 13.7mm)	

Supplier Device Package	-
Control Features	-
	Report errors?

V375A36T500B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

V375A36T500B Payment Methods





















V375A36T500B Shipping Methods













If you have any question about V375A36T500B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com