



V375A54M600BS2 Information

Heisener.com

Part Number V375A54M600BS2
Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 54V 600W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









V375A54M600BS2 Specifications

Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 54V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11.11A Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Manufacturer Part Number	V375A54M600BS2
DC DC Converters	Manufacturer	Vicor Corporation
Package Full Brick Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 54V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11.11A Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Category	Power Supplies - Board Mount
Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 54V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11.11A Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 54V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11.11A Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 54V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11.11A Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Series	Maxi
Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 54V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11.11A Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Туре	Isolated Module
Voltage - Input (Max) 425V Voltage - Output 1 54V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11.11A Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Number of Outputs	1
Voltage - Output 1 54V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11.11A Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Voltage - Input (Min)	250V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11.11A Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Voltage - Input (Max)	425V
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11.11A Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Voltage - Output 1	54V
Voltage - Output 4 - Current - Output (Max) 11.11A Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Voltage - Output 3	-
Power (Watts) 600W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Voltage - Output 4	-
Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO	Current - Output (Max)	11.11A
Applications ITE (Commercial) Features OVP, UVLO	Power (Watts)	600W
Features OVP, UVLO	Voltage - Isolation	3kV (3000V)
· ·	Applications	ITE (Commercial)
C .: T	Features	OVP, UVLO
Operating Temperature -55°C ~ 100°C	Operating Temperature	-55°C ~ 100°C
Efficiency 89.6%	Efficiency	89.6%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 2.20" W x 0.54" H (116.8mm x 55.9mm x 13.7mm)	Size / Dimension	4.60" L x 2.20" W x 0.54" H (116.8mm x 55.9mm x 13.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

V375A54M600BS2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

V375A54M600BS2 Payment Methods



















V375A54M600BS2 Shipping Methods













If you have any question about V375A54M600BS2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com