



V375A8M400BS Information

Heisener.com

Part Number V375A8M400BS Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 8V 400W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









V375A8M400BS Specifications

Manufacturer V375A8M400BS Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 8V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50A Power (Watts) 400W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole Package / Case Full Brick		
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50A Power (Watts) 400W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Manufacturer Part Number	V375A8M400BS
DC DC Converters Package Full Brick Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50A Power (Watts) 400W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Manufacturer	Vicor Corporation
Package Full Brick Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50A Power (Watts) 400W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Category	Power Supplies - Board Mount
Series Maxi Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50A Power (Watts) 400W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50A Power (Watts) 400W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50A Power (Watts) 400W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Series	Maxi
Voltage - Input (Min) 250V Voltage - Input (Max) 425V Voltage - Output 1 8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50A Power (Watts) 400W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Туре	Isolated Module
Voltage - Input (Max) 425V Voltage - Output 1 8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50A Power (Watts) 400W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Number of Outputs	1
Voltage - Output 1 8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50A Power (Watts) 400W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Voltage - Input (Min)	250V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50A Power (Watts) 400W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Voltage - Input (Max)	425V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OVP, UVLO Operating Temperature Efficiency 82.8% Mounting Type Through Hole	Voltage - Output 1	8V
Voltage - Output 4 Current - Output (Max) Fower (Watts) Voltage - Isolation Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Voltage - Output 2	-
Current - Output (Max) 50A Power (Watts) 400W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Voltage - Output 3	-
Power (Watts) $400W$ Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)Features $OVP, UVLO$ Operating Temperature $-55^{\circ}C \sim 100^{\circ}C$ Efficiency 82.8% Mounting TypeThrough Hole	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOVP, UVLOOperating Temperature $-55^{\circ}C \sim 100^{\circ}C$ Efficiency 82.8% Mounting TypeThrough Hole	Current - Output (Max)	50A
Applications ITE (Commercial) Features OVP, UVLO Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Power (Watts)	400W
Features OVP, UVLO Operating Temperature $-55^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Efficiency 82.8% Mounting Type Through Hole	Voltage - Isolation	3kV (3000V)
Operating Temperature -55°C ~ 100°C Efficiency 82.8% Mounting Type Through Hole	Applications	ITE (Commercial)
Efficiency 82.8% Mounting Type Through Hole	Features	OVP, UVLO
Mounting Type Through Hole	Operating Temperature	-55°C ~ 100°C
	Efficiency	82.8%
Package / Case Full Brick	Mounting Type	Through Hole
Tuesday Case	Package / Case	Full Brick
Size / Dimension 4.60" L x 2.20" W x 0.54" H (116.8mm x 55.9mm x 13.7mm)	Size / Dimension	4.60" L x 2.20" W x 0.54" H (116.8mm x 55.9mm x 13.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

V375A8M400BS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

V375A8M400BS Payment Methods



















V375A8M400BS Shipping Methods













If you have any question about V375A8M400BS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com