

VAOL-S1513RGB

VAOL-S1513RGB Information

www.thelsener.com	 VAOL-S1513RGB Visual Communications Company - VCC Optoelectronics LED Indication - Discrete LED RGB CLEAR 4SMD 4-SMD, No Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VAOL-S1513RGB Specifications

ManufacturerVisual Communications Company - VCCCategoryOptoelectronicsLED Indication - DiscretePackage4-SMD, No LeadSeries-ColorRed, Green, Blue (RGB)ConfigurationCommon AnodeLens ColorColorlessLens Style/SizeRectangle with Flat Top, 2.00mm x 2.60mmVoltage - Forward (Vf) (Typ)2V Red, 3.3V Green, 3.3V BlueVoltage - Forward (Vf) (Typ)20°Viewing Angle100°Wavelength - Dominant624nm Red, 525nm Green, 470nm BlueWavelength - Peak632nm Red, 518nm Green, 468nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.20mm L x 2.60mm WHeight (Max)1.10mm		
CategoryOptoelectronicsLED Indication - DiscretePackage4-SMD, No LeadSeries-ColorRed, Green, Blue (RGB)ConfigurationCommon AnodeLens ColorColorlessLens TransparencyClearMillicandela Rating140mcd Red, 180mcd Green, 70mcd BlueLens Style/SizeRectangle with Flat Top, 2.00mm x 2.60mmVoltage - Forward (Vf) (Typ)2V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountGaum Red, 525nm Green, 470nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.20mm L x 2.60mm WHeight (Max)1.10mm	Manufacturer Part Number	VAOL-S1513RGB
LED Indication - DiscretePackage4-SMD, No LeadSeries-ColorRed, Green, Blue (RGB)ConfigurationCommon AnodeLens ColorColorlessLens TransparencyClearMillicandela Rating140mcd Red, 180mcd Green, 70mcd BlueLens Style/SizeRectangle with Flat Top, 2.00mm x 2.60mmVoltage - Forward (Vf) (Typ)2V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueFeatures-Package / Case4-SMD, No LeadSurplier Device Package4-SMDSize / Dimension3.20mm L x 2.60mm WHeight (Max)1.10mm	Manufacturer	Visual Communications Company - VCC
Package4-SMD, No LeadSeries-ColorRed, Green, Blue (RGB)ConfigurationCommon AnodeLens ColorColorlessLens TransparencyClearMillicandela Rating140mcd Red, 180mcd Green, 70mcd BlueLens Style/SizeRectangle with Flat Top, 2.00mm x 2.60mmVoltage - Forward (Vf) (Typ)2V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueFeatures-Package / Case4-SMD, No LeadSurplier Device Package4-SMDSize / Dimension3.20mm L x 2.60mm WHeight (Max)1.10mm	Category	Optoelectronics
Series-ColorRed, Green, Blue (RGB)ConfigurationCommon AnodeLens ColorColorlessLens TransparencyClearMillicandela Rating140mcd Red, 180mcd Green, 70mcd BlueLens Style/SizeRectangle with Flat Top, 2.00mm x 2.60mmVoltage - Forward (Vf) (Typ)2V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package3.20mm L x 2.60mm WHeight (Max)1.10mm		LED Indication - Discrete
ColorRed, Green, Blue (RGB)ConfigurationCommon AnodeLens ColorColorlessLens TransparencyClearMillicandela Rating140mcd Red, 180mcd Green, 70mcd BlueLens Style/SizeRectangle with Flat Top, 2.00mm x 2.60mmVoltage - Forward (Vf) (Typ)2V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package3.20mm L x 2.60mm WHeight (Max)1.10mm	Package	4-SMD, No Lead
ConfigurationCommon AnodeLens ColorColorlessLens TransparencyClearMillicandela Rating140mcd Red, 180mcd Green, 70mcd BlueLens Style/SizeRectangle with Flat Top, 2.00mm x 2.60mmVoltage - Forward (Vf) (Typ)2V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueVateres-Package / Case4.SMD, No LeadSupplier Device Package4.SMDSize / Dimension3.20mm L x 2.60mm WHeight (Max)1.10mm	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating140mcd Red, 180mcd Green, 70mcd BlueLens Style/SizeRectangle with Flat Top, 2.00mm x 2.60mmVoltage - Forward (Vf) (Typ)2V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueCurrent - Test20°Mounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueVavelength - Peak632nm Red, 518nm Green, 468nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package3.20mm L x 2.60mm WHeight (Max)1.10mm	Color	Red, Green, Blue (RGB)
Lens TransparencyClearMillicandela Rating140mcd Red, 180mcd Green, 70mcd BlueLens Style/SizeRectangle with Flat Top, 2.00mm x 2.60mmVoltage - Forward (Vf) (Typ)2V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueFeatures-Package / Case4.SMD, No LeadSupplier Device Package3.20mm L x 2.60mm WBize / Dimension1.10mm	Configuration	Common Anode
Millicandela Rating140mcd Red, 180mcd Green, 70mcd BlueLens Style/SizeRectangle with Flat Top, 2.00mm x 2.60mmVoltage - Forward (Vf) (Typ)2V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueWavelength - Peak632nm Red, 518nm Green, 468nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package3.20mm L x 2.60mm WHeight (Max)1.10mm	Lens Color	Colorless
Lens Style/SizeRectangle with Flat Top, 2.00mm x 2.60mmVoltage - Forward (Vf) (Typ)2V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueWavelength - Peak632nm Red, 518nm Green, 468nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package3.20mm L x 2.60mm WHeight (Max)1.10mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ)2V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueWavelength - Peak632nm Red, 518nm Green, 468nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package3.20mm L x 2.60mm WKieght (Max)1.10mm	Millicandela Rating	140mcd Red, 180mcd Green, 70mcd Blue
Current - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueWavelength - Peak632nm Red, 518nm Green, 468nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package3.20mm L x 2.60mm WHeight (Max)1.10mm	Lens Style/Size	Rectangle with Flat Top, 2.00mm x 2.60mm
Viewing Angle120°Mounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueWavelength - Peak632nm Red, 518nm Green, 468nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.20mm L x 2.60mm WHeight (Max)1.10mm	Voltage - Forward (Vf) (Typ)	2V Red, 3.3V Green, 3.3V Blue
Nounting TypeSurface MountWavelength - Dominant624nm Red, 525nm Green, 470nm BlueWavelength - Peak632nm Red, 518nm Green, 468nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.20mm L x 2.60mm WHeight (Max)1.10mm	Current - Test	20mA Red, 20mA Green, 20mA Blue
Wavelength - Dominant624nm Red, 525nm Green, 470nm BlueWavelength - Peak632nm Red, 518nm Green, 468nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.20mm L x 2.60mm WHeight (Max)1.10mm	Viewing Angle	120°
Wavelength - Peak632nm Red, 518nm Green, 468nm BlueFeatures-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.20mm L x 2.60mm WHeight (Max)1.10mm	Mounting Type	Surface Mount
Features-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.20mm L x 2.60mm WHeight (Max)1.10mm	Wavelength - Dominant	624nm Red, 525nm Green, 470nm Blue
Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.20mm L x 2.60mm WHeight (Max)1.10mm	Wavelength - Peak	632nm Red, 518nm Green, 468nm Blue
Supplier Device Package4-SMDSize / Dimension3.20mm L x 2.60mm WHeight (Max)1.10mm	Features	-
Size / Dimension 3.20mm L x 2.60mm W Height (Max) 1.10mm	Package / Case	4-SMD, No Lead
Height (Max) 1.10mm	Supplier Device Package	4-SMD
	Size / Dimension	3.20mm L x 2.60mm W
Report errors?	Height (Max)	1.10mm
Report criois.		Report errors?

VAOL-S1513RGB Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

VAOL-S1513RGB Payment Methods



VAOL-S1513RGB Shipping Methods



If you have any question about VAOL-S1513RGB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com