



VCE05US05 Information



For Reference Only

Part Number VCE05US05
Manufacturer XP Power

Category Power Supplies - Board Mount

AC DC Converters

Description AC-DC, 5W, P 1X1", PCB MOUNT, EN

Package 4-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VCE05US05 Specifications

Manufacturer Part Number VCE0SUS05 Manufacturer XP Power Category Power Supplies - Board Mount AC DC Converters Package 4-DIP Module Series VCE05 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Applications ITE (Commercial) Features Universal Input Operating Temperature -25°C ~ 70°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm) Report errors?		
Category Power Supplies - Board Mount AC DC Converters Package 4-DIP Module Series VCE05 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 5W Applications ITE (Commercial) Features Universal Input Operating Temperature -25°C ~ 70°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Manufacturer Part Number	VCE05US05
Package 4-DIP Module Series VCE05 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 5W Applications ITE (Commercial) Features Universal Input Operating Temperature -25°C ~ 70°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Manufacturer	XP Power
Package 4-DIP Module Series VCE05 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 5W Applications ITE (Commercial) Features Universal Input Operating Temperature -25 °C ~ 70 °C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30 " L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Category	Power Supplies - Board Mount
Series VCE05 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 5W Applications ITE (Commercial) Features Universal Input Operating Temperature -25°C ~ 70°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 5W Applications ITE (Commercial) Features Universal Input Operating Temperature -25°C ~ 70°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Package	4-DIP Module
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 5W Applications ITE (Commercial) Features Universal Input Operating Temperature -25°C ~ 70°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Series	VCE05
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 5W Applications ITE (Commercial) Features Universal Input Operating Temperature -25°C ~ 70°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Туре	Enclosed
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features Universal Input Operating Temperature Efficiency Mounting Type Through Hole Package / Case Size / Dimension 5V - Current - Output (Max) - DA - SU - Through Hole 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Features Universal Input Operating Temperature Efficiency Mounting Type Through Hole Package / Case Size / Dimension - - - - - - - - - - - - -	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Features Universal Input Operating Temperature Efficiency Mounting Type Through Hole Package / Case Size / Dimension - Current - Output (Max) IA - Current - Output (Max) ITE (Commercial) ITE (Commercial) ITE (Commercial) Features Universal Input - 25°C ~ 70°C (With Derating) - Through Hole 1 - Current - Output (Max) -	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features Universal Input Operating Temperature -25°C ~ 70°C (With Derating) Efficiency Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features Universal Input Operating Temperature -25°C ~ 70°C (With Derating) Efficiency Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Voltage - Output 3	-
Power (Watts) 5W Applications ITE (Commercial) Features Universal Input Operating Temperature -25°C ~ 70°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Voltage - Output 4	-
Applications ITE (Commercial) Features Universal Input Operating Temperature -25°C ~ 70°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Current - Output (Max)	1A
Features Universal Input Operating Temperature -25°C ~ 70°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Power (Watts)	5W
Operating Temperature -25°C ~ 70°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Applications	ITE (Commercial)
Efficiency - Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Features	Universal Input
Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Operating Temperature	$-25^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Package / Case 4-DIP Module Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Efficiency	-
Size / Dimension 1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)	Mounting Type	Through Hole
	Package / Case	4-DIP Module
Report errors?	Size / Dimension	1.30" L x 1.10" W x 0.75" H (33.0mm x 27.9mm x 19.1mm)
		Report errors?

VCE05US05 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VCE05US05 Payment Methods



















VCE05US05 Shipping Methods













If you have any question about VCE05US05, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com