



VCS70US15 Information



For Reference Only

Part Number VCS70US15
Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 15V 70W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VCS70US15 Specifications

Manufacturer Part Number VCS70US15 Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VCS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.67A Power (Watts) 70W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VCS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.67 A Power (Watts) 70W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Manufacturer Part Number	VCS70US15
Package - Series VCS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.67A Power (Watts) 70W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Manufacturer	XP Power
Package - Series VCS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.67A Power (Watts) 70W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series VCS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.67A Power (Watts) 70W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.67A Power (Watts) 70W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.67A Power (Watts) 70W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Series	VCS
Voltage - Input85 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)4.67APower (Watts)70WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency87%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Туре	Enclosed
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Strict (Source of Source of Sou	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Size / Dimension - Universal Size / Dimension - Courrent - Output (Max) -	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Size / Dimension - 25°C ~ 70°C (With Derating) Size / Dimension - 25°C ~ 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Voltage - Output 1	15V
Voltage - Output 4 Current - Output (Max) 4.67A Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 70W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency 87% Operating Temperature $-25^{\circ}C \sim 70^{\circ}C$ (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension $5.12"$ L x $3.88"$ W x $1.61"$ H $(130.0mm$ x $98.5mm$ x $41.0mm$)	Current - Output (Max)	4.67A
Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Power (Watts)	70W
Efficiency 87% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Applications	ITE (Commercial)
Operating Temperature -25°C ~ 70°C (With Derating) Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Efficiency	87%
Mounting Type Chassis Mount Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Operating Temperature	-25°C ~ 70°C (With Derating)
Size / Dimension 5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)	Features	Adjustable Output, DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.12" L x 3.88" W x 1.61" H (130.0mm x 98.5mm x 41.0mm)
		Report errors?

VCS70US15 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VCS70US15 Payment Methods


































If you have any question about VCS70US15, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com